



Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	24 V
Product or component type	Replacement battery cartridge
Main Output Voltage	24 V
Battery type	Lead-acid battery
Provided equipment	User manual

Batteries & Runtime

Battery location	Internal battery
Number of battery blocks per string	6
Number of battery free slots	0
Number of battery filled slots	0
Device mounting	Built-in
Battery voltage	24 V
Number of battery replacement quantity	2

Physical

Colour	Black
Height	151 mm
Width	99 mm
Depth	132 mm
Net weight	4.3 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

Output

Battery capacity	7 Ah
------------------	------

Conformance

Product certifications	UL 1778 5th edition
Standards	UL 1778 5th edition

## Environmental

Ambient air temperature for operation	0...40 °C
Operating altitude	0...10000 ft
Relative humidity	0...85 %
Ambient air temperature for storage	-15...50 °C
Storage altitude	0.00...3048.00 m
Storage Relative Humidity	0...95 %

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	19.5 cm
Package 1 Width	39.5 cm
Package 1 Length	49.5 cm
Package 1 Weight	18.9 kg
SCC14	50731304427501

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#"> REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#"> EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#"> China RoHS Declaration</a>
RoHS exemption information	<a href="#"> Yes</a>
Environmental Disclosure	<a href="#"> Product Environmental Profile</a>
Circularity Profile	<a href="#"> End Of Life Information</a>

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------