

Features

- Push-pull latching system
- Chrome plated Brass
- IP68
- 360° Screening for full EMC shielding

RS PRO Industrial Circular Connectors

RS Stock No.: 2406433



RS PRO is the own brand of RS. The RS PRO Seal of Approval is your assurance of professional quality, a guarantee that every part is rigorously tested, inspected, and audited against demanding standards. Making RS PRO the Smart Choice for our customers.

Industrial Circular Connectors



Product Description

RS Pro's range of waterproof Chrome plated Brass push-pull locking connectors offer exceptional quality that is found in many cutting-edge connectors, including an IP68 rating and full 360° EMC shielding with a high mating life. As has become standard within the RS Pro brand you can expect high quality products but at a reasonable price. These connectors are ideal for use in medical devices, testing equipment, audio equipment and other high-end applications.

General Specifications

Number of Contacts	16					
Housing Material	Chrome Plated Brass					
Contact Material	Brass					
Contact Plating	Gold					
Contact Gender	Female					
Mating Type	Cable Mount					
Body Orientation	Straight					
Contact Carrier	PPS					
Mating Cycles	>5,000					
Colour	Natural					
Application	Instrumentation, Process control, Robotics, Assembly lines and manufacturing, Factory automation, Industrial production and automation, Medical devices					

Electrical Specifications

Plug/Socket	Socket
Current Rating	4A
Test Voltage Contact-Shell k/vAC	1.0
Test Voltage Contact – Contact k/v AC	1.50

Mechanical Specifications

Connector Size	2F
Termination Method	Solder
Mounting Type	Panel Mount
Panel Cut-Out	16mm

Industrial Circular Connectors



Operation Environment Specifications

Operating Temperature	-55°C to +250°C
1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	

Protection Category

ID Dating	IDCO
IP Rating	IP68

Approvals

Compliance/Certifications	RoHS, CE
---------------------------	----------

FOR MATING PARTS, SEE MATRIX:



RM-F Series 2F

Plug Cable End			Panel Mount				In-Line Cable End			
RS Stock No.	No. of Contacts	Gender	Mates With	RS Stock No.	No. of Contacts	Gender		RS Stock No.	No. of Contacts	Gender
2406580	2	Male		2406427	2	Female	Or	2406511	2	Female
2406581	3	Male		2406428	3	Female		2406512	3	Female
2406582	4	Male		2406429	4	Female	W.	2406513	4	Female
2406583	6	Male		2406430	6	Female	-	2406514	6	Female
2406584	8	Male		2406431	8	Female		2406515	8	Female
2406585	1+8	Male		2406432	1+8	Female		2406516	1+8	Female
2406586	16	Male		2406433	16	Female		2406518	16	Female
2406587	19	Male	0.400	2406434	19	Female	95	2406519	19	Female

The RS PRO Seal of Approval is only awarded after a rigorous quality process to demanding international standards.



Industrial Circular Connectors



