



Datasheet

## RS Pro Flow Controller, 15mm Tube Inlet Port

RS Stock No: **511-3943**



### Product Details

RS Pro fitting has 15 mm tube inlet port. It withstands outlet pressure up to 15 bar. This fitting offers connection through 3/4 Inch BSP threaded port. It also accepts 15 mm compression fittings.

### Features and Benefits

- Polysulphone bodied flowmeters
- Open collector (NPN) pulse output proportional to flow rate
- Non-metallic fittings, PVDF, available for pure water or aggressive chemicals
- Robust sapphire bearings
- Traceable calibration certificate
- Hall effect detection suitable for used with opaque liquids



ENGLISH

### Specifications:

Body Material	PSU
Inlet Port Type	Tube
Outlet Port Type	Threaded
Threaded Outlet Port	BSP 3/4 in
Threaded Outlet Thread Gender	Male
Threaded Outlet Thread Standard	BSP
Maximum Outlet Pressure	15 bar
Tube Inlet Port	15 mm
Threaded Outlet Thread Size	3/4 in
Type	Non-Metallic Fitting
Flow Rate	6.0 to 100 l/min
Length	124 mm
Maximum Temperature	+125°C
Minimum Temperature	-25°C
Operating Temperature Range	-25 to +125°C