

FEATURES

- IP67
- Pre-wired with 500 mm partially stripped cable
- Straight plugs and sockets
- 4, 5, 8 and 12 pole versions

RS PRO M12 MALE FRONT PANEL MOUNT CONNECTOR 12 PIN 500MM PVC CABLE

RS Stock No.: 2500743



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description
ATTRIBUTE 1

RS Pro M12 Panel Mount Connectors

From RS PRO, a selection of M12 circular connectors designed for panel mounting. The sensor style connectors have an M12 threaded interface and industry standard A coding preventing miss-mating. Conveniently pre-terminated with partially stripped wires the RS PRO range is easy to incorporate into any automation or sensory application. With an IP67 ingress rating, the RS PRO panel mount connectors are ideally suited to harsh environments that demand a more rugged connection solution.

Features & Benefits

- IP67
- Nylon 66 contact carrier
- PG9 clamp nut
- Pre-wired with 500 mm partially stripped cable
- Straight plugs and sockets
- 4, 5, 8 and 12 pole versions

Applications

The RS PRO series of M12 panel mount connectors are generally used in industrial applications. They are typically used when connecting to sensors and actuators. Some of the most popular areas are

- Instrumentation
- Process control
- Robotics
- Assembly lines
- Factory automation
- Industrial automation

General Specifications

| | |
|---------------------------|-----------------|
| Rated Operational Voltage | 30 V |
| Current Rating | 1.5A |
| Insulation Resistance | >= 100 MΩ |
| Temperature Range | -25°C ... +75°C |
| Mounting | Front (M12 x 1) |
| Coding | A-Coded |

Material Specifications

| | |
|------------------|-----------------|
| Housing Material | Brass Ni Plated |
| Contact | Cu-Zn |
| Contact Plating | Gold Flash |
| Contact Carrier | Nylon 66 |
| O-Ring | Neoprene |
| Pole | 12 |
| Clamp Nut | PG9 |

Cable Specifications

| | |
|-----------------------|--------------------|
| Cable Length-L | 500 mm |
| Cross Section of Wire | 0.14 sq. mm |
| Cable Type | PVC |
| Termination | Partially Stripped |

Protection Category

| | |
|----------------------|------|
| Degree of Protection | IP67 |
|----------------------|------|


Additional Information

| | |
|----------------------|----------|
| Custom Tariff Number | 85369090 |
|----------------------|----------|


Approvals

| | |
|---------------|-----------------|
| Standards Met | IEC 61076-2-101 |
|---------------|-----------------|

Connection Diagrams / Assembly Diagrams / Illustrations / Accessories



All Dimensions are in mm.



| Pin No. | Description |
|---------|-------------|
| 1 | Brown |
| 2 | Blue |
| 3 | White |
| 4 | Green |
| 5 | Pink |
| 6 | Yellow |
| 7 | Black |
| 8 | Grey |
| 9 | Red |
| 10 | Violet |
| 11 | Grey / Pink |
| 12 | Red / Blue |