

FEATURES

- Abrasion, ozone and weather resistant
- Smooth rubber NBR / SBR construction
- In accordance with EN ISO 2398
- Wide temperature range -40°C to +90°C
- Safety factor 3:1

RS PRO Air Hose Black NBR, SBR 21mm x 25m

RS Stock No.: 914-5534



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

Brought to you by RS Pro, a range of rubber air hoses, manufactured from a textile reinforced NBR/SBR synthetic rubber. Being Weather and ozone resistant, it is suitable for medium duty applications such as pneumatic air tools and compressors used in the construction and automotive industry and general workshop use. All models are highly reliable and excellent quality.

General Specifications

Colour	Black
Material	NBR, SBR
Number Of Tubes	1
Application	Compressed Air Tools

Mechanical Specifications

Hose Inside Diameter	13mm
Hose Outside Diameter	21mm
Length	25m
Weight Per Metre	0.43kg
Bend Radius	130mm

Operation Environment Specifications

Maximum Operating Pressure	20 bar
Minimum Operating Temperature	-40°C
Maximum Operating Temperature	+90°C
Burst Pressure	60 bar

Approvals**Compliance/Certifications**

EN ISO 2398

RS Stock Number	Internal Diameter	External Diameter	Length	Weight per Meter	Max Working Pressure	Burst Pressure	Bend Radius
9145540	6 mm	12 mm	25 m	0.18 kg	20 bar	60 bar	60 mm
9145543	8 mm	15 mm	25 m	0.23 kg	20 bar	60 bar	80 mm
9145525	10 mm	17 mm	25 m	0.29 kg	20 bar	60 bar	100 mm
9145534	13 mm	21 mm	25 m	0.43 kg	20 bar	60 bar	130 mm
9145537	19 mm	29 mm	25 m	0.7 kg	20 bar	60 bar	190 mm
9145531	25 mm	36 mm	25 m	1.0 kg	20 bar	60 bar	250 mm