



### SPECIFICATION

Model		2163790	2163791
1	N° OF POLE	8	8
2	N° OF PHASE	3	3
3	RATED VOLTAGE	V	24
4	RATED SPEED	rpm	4500
5	RATED TORQUE	Nm	0,07
6	MAX PEAK TORQUE	Nm	0,21
7	TORQUE CONSTANT	Nm/A	0,037
8	LINE TO LINE RESISTANCE	$\Omega$	1,1
9	LINE TO LINE INDUCTANCE	mH	1,2
10	NO-LOAD CURRENT	mA	270
11	MAX PEAK CURRENT	A	5,3
12	RATED CURRENT	A	1,89
13	LENGTH	mm	57
14	ROTOR INERTIA	g-cm <sup>2</sup>	27
15	WEIGHT	Kg	0,25



### CONNECTION

Lead N°	Color	Gauge	Function
1	RED	UL1430 AWG26	VCC HALL SENSOR +5 TO +24 VDC
2	BLUE	UL1430 AWG26	HALL A
3	GREEN	UL1430 AWG26	HALL B
4	WHITE	UL1430 AWG26	HALL C
5	BLACK	UL1430 AWG26	HALL SENSOR GROUND
6	YELLOW	UL1332 AWG24	PHASE U
7	BROWN	UL1332 AWG24	PHASE V
8	ORANGE	UL1332 AWG24	PHASE W

### CHARACTERISTICS

Item	
HALL EFFECT ANGLE	120°
SHAFT RUN OUT	0,025 mm
INSULATION CLASS	B
RADIAL PLAY (450 g LOAD)	0,02 mm
AXIAL PLAY (450 g LOAD)	0,08 mm
MAX RADIAL FORCE (10 MM FROM FRONT FLANGE)	15N
MAX AXIAL FORCE	10N
DIELECTRIC STRENGTH	600 VCA FOR ONE SECOND
INSULATION RESISTANCE	100 Mohm min. 500 VDC