

FEATURES

- Front panel mount
- Thermoplastic body
- Black short lever
- Non-illuminated
- Switch position: 2 or 3
- Contact Configuration: 1NO or 1NO+1NC available
- Support base
- Connecting Terminals: Screw with captive cable clamp
- Switch Actuation: 2 or 3
- Cut-out Diameter: 22.5 mm
- Outer diameter: 30 mm
- IP20, IP65 rating
-

RS PRO Key-Operated Selector Switch

RS Stock No.: 2383963



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Family Name

Product Description

These selector switches are complete units made from the highest quality materials and include a key operated selector switch head, contact block, and support base. Upon inspection, the selector switch heads are non-illuminated and have a thermoplastic body and short lever actuator. The contact blocks are available in multiple contact configurations with 2 or 3 switch positions and the support base mounts securely into panels up to 6mm thick eliminating movement in the mounting hole.

General Specifications

Casing Material	Thermoplastic
Operator	Short lever selector switches 2383943 – 2 stable positions left and right key extraction
Color	Black
Outer diameter	30
Microswitch	1NO
Connecting Terminals	Screw with captive cable clamp
Connecting Cables Dimensions [mm ²]	1 or 2 conductors - 0.5 ... 2.5

Mechanical Specifications

Operating Temperatures [°C]	-25 / +70
Stock Temperatures [°C]	-40 / +80
Mechanical durability (Millions of operations)	0.3
B10d (million of operations)	0.6
Max. switching frequency [Cicli/h]	3600

Electrical Specifications

Protection against electrical shocks	Class II - Double insulation
Rated Insulating Voltage Ui [V]	690
Pollution Degree	3
Contact rating secondo UL508	A 600 Q 300
Rated impulsive voltage [kV]	8
Conventional thermal current in air free I _{th} (θ min 40 ° C) [A (θ	10

Family Name

Short circuit protection (EU min 500Vac - fuses type gG (gl)) [A]	10
Rated Operational Current I _e - AC-15 (50-60 Hz) [Vac - A]	24V - 10A / 240V - 6A / 400V - 4A
Rated Operational Current DC-13 [Vdc - A]	24V - 2,8A / 125V - 0.55A / 250V - 0.27A
Resistance Between Contacts [mΩ]	25

Protection Category

IP Degree of Protection	65 (front panel) 20 (rear panel)
-------------------------	----------------------------------

Additional Information

EAN	8000126233360
Custom Tariff Number	85371098

Classification

eCI@ss (Version)	
UNSPSC (Version)	

Approvals

Declarations	CE – UKCA
Standards Met	EN 60947-5-1 and UL 508

Similar Products

Stock No.	Brand	Product Name	Attribute 1	Attribute 2	Attribute 3
XXX-XXXX	RS PRO				
XXX-XXXX	RS PRO				



Connection Diagrams / Assembly Diagrams / Illustrations / Accessories