

Datasheet

RS Pro Din Rail Terminal, CDU 6 series, 600 V (UL/CSA), 800 V (IEC), 50 A (UL/CSA), 57 A (IEC), Screw Termination
RS Stock No: **878-7547**



Product Details

RS Pro DIN rail terminal has a voltage rating of 600 V (UL/CSA), 800 V (IEC) and current rating of 50 A (UL/CSA), 57 A (IEC). This single level, screw termination block offers excellent vibration resistance and is suitable for a broad range of cross-section and wire types. This highly reliable block is easy to handle and safe to connect. The DIN rail terminal meets UL and CSA standards.

Features and Benefits

- Mini DIN rail mounted screw clamp terminal blocks
- Suitable for a broad range of cross-section and wire types
- Wires can be connected without any special preparations
- Easy to handle and safe to connect
- Excellent vibration resistance
- High reliability and maintenance free
- Very low contact resistance
- Easy mounting and dismounting from DIN rail



Specifications:

Current Rating	50 A (CSA), 57 A (IEC), 50 A (UL)
Number of Levels	Single
Termination Method	Screw
Voltage Rating	600 V (CSA), 800 V (IEC), 600 V (UL)
Wire Size	26 to 8 AWG
Dimensions	42.5 x 8 x 47.5 mm
Material	Nylon 66 Housing
Standards Met	UL, CSA, IEC