A9A26929

Auxiliary contact, Acti9, iOF/SD+OF, 2OC, AC/DC





Main

Range of product	Acti9
Product or component type	Double OC or fault contact
Device short name	iOF/SD+OF
Signal contacts composition	2 C/O
[In] rated current	DC-12 1 A at 130 V, DC DC-12 1.5 A at 60 V, DC DC-12 2 A at 48 V, DC DC-12 6 A at 24 V, DC AC-12 3 A at 415 V, AC 50/60 Hz AC-12 6 A at 240 V, AC 50/60 Hz
9 mm pitches	1

Complementary

[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	4 kV
Local signalling	Mechanical indicator
Mounting mode	Fixed
Mounting support	DIN rail
Comb busbar and distribution block compatibility	NO
Height	90 mm
Width	9 mm
Depth	73 mm
Product weight	43 g
Colour	White
Connections - terminals	Screw clamp terminal (top and bottom) 2 cable(s) 2.5 mm² - rigid Screw clamp terminal (top and bottom) 2 cable(s) 1.5 mm² - flexible with ferrule Screw clamp terminal (top and bottom) 1 cable(s) 0.52.5 mm² - flexible Screw clamp terminal (top and bottom) 1 cable(s) 14 mm² - rigid
Wire stripping length	10 mm
Tightening torque	1 N.m

Environment

Standards	EN/IEC 60947-5-1	
Tropicalisation	2 conforming to EN/IEC 60947-5-1	
Ambient air temperature for operation	-3570 °C	
Ambient air temperature for storage	-4085 °C	

Packing Units

· doming of the		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	7.500 cm	
Package 1 Width	2.400 cm	
Package 1 Length	9.200 cm	
Package 1 Weight	50.000 g	
Unit Type of Package 2	BB1	
Number of Units in Package 2	12	
Package 2 Height	8.500 cm	

Package 2 Width	10.000 cm
Package 2 Length	27.000 cm
Package 2 Weight	693.000 g
Unit Type of Package 3	S03
Number of Units in Package 3	120
Package 3 Height	30.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	7.600 kg

Offer Sustainability

Green Premium product
☑ REACh Declaration
Yes
Compliant EPEU RoHS Declaration
Yes
Yes
China RoHS Declaration
₽¥Yes
Product Environmental Profile
☑ End Of Life Information
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months	