

FEATURES

- Various threads are available
- Completely sealed
 against dust
- Excellent water
 resistance
- Made with high quality Nylon 66
- Locknut supplied

RS PRO M25 Cable Gland with Locknut, Nylon, IP68

RS Stock No.: 822-9745



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.



Product Description

Brought to you by RS PRO, a range of metric threaded cable glands offering excellent strain relief and cable protection. Cable glands allow you to mount a cable into a pre-drilled hole. Commonly used within construction and by electrical engineers, cable glands are simple and easy to use. Each gland is rated as IP68, ensuring the level of cable protection is incredibly resilient to the outdoors and other harsh environments. All models are highly reliable and excellent quality.

General Specifications

Thread Size	M25
Material	Nylon 66
Colour	Grey
Locknut Included	Yes
Pack size	10
Application	Machinery with delicate internals, Telecommunications, Flow meters, Underwater power generators

Mechanical Specifications

Maximum Cable Diameter	18mm
Minimum Cable Diameter	13mm
Thread Length L2	29.4mm
Seals B1	18.4mm
Protrusion Length L1	15.2mm
Nut L3	22.3mm
Thread inner diameter D2	18.6mm
Thread outer diameter D1	25mm

Cable Glands



Operation Environment Specifications

Minimum Operating Temperature	-60°C
Maximum Operating Temperature	85°C
Operating Temperature Range	-60 to +85°C

Protection Category		
IP Rating	IP68	

Approvals	
Compliance/Certifications	EN 61340
Standards Met	UL 94 V-2



Cable Glands



RS PART NUMBER	DESCRIPTION	D1	D2	B1	L1	L2	L3	Cable Range	COLOR	Packsize
8229739	round topCable GlandM12 × 1.5 Grey IP68	12	8.3	6.9	7.9	19.6	13.6	3~6.5		
8229748	round topCable GlandM16 × 1.5 Grey IP68	16	10.9	10.5	15.5	23.4	16.9	5~10	1	
8229741	round topCable GlandM20 × 1.5 Grey IP68	20	15	14	15	28.5	18.5	10~14		
8229757	round topCable GlandM20S × 1.5 GreyIP68	20	15	14	10	28.5	18.5	10~14	GREY	
8229745	round topCable GlandM25 × 1.5 Grey IP68	25	18.6	18.4	15.2	29.4	22.3	13~18	1	
8229751	round topCable GlandM25S × 1.5 Grey IP68	25	18.6	18.4	10	29.4	22.3	13~18		
8229754	round topCable GlandM32 × 1.5 Grey IP68	32	26	25	14.7	34.5	25.7	18~25		
8229767	round topCable GlandM16 × 1.5 White IP68	16	10.9	10.5	15.5	23.4	16.9	5~10		
8229776	round topCable GlandM20 × 1.5 White IP68	20	15	14	15	28.5	18.5	10~14	1	10
8229782	round topCable GlandM20S × 1.5 WhiteIP68	20	15	14	10	28.5	18.5	10~14	VALUTE	
8229779	round topCable GlandM25 × 1.5 White IP68	25	18.6	18.4	15.2	29.4	22.3	13~18	WHITE	
8229785	round topCable GlandM25S × 1.5 WhiteIP68	25	18.6	18.4	10	29.4	22.3	13~18		
8229773	round topCable GlandM32 × 1.5 White IP68	32	26	25	14.7	34.5	25.7	18~25	1	
8229760	round topCable GlandM20S × 1.5 BlacklP68	20	15	14	10	28.5	18.5	10~14	DLACK	
8229763	round topCable GlandM25S × 1.5 BlackIP68	25	18.6	18.4	10	29.4	22.3	13~18	BLACK	
8229789	round topCable GlandM20 × 1.5 Red IP68	20	15	14	15	28.5	18.5	10~14	RED	
8229798	round topCable GlandM25 × 1.5 Red IP68	25	18.6	18.4	15.2	29.4	22.3	13~18		

