

Eaton FWC-32A10F

Catalog Number: FWC-32A10F

Eaton Bussmann series FWC high speed cylindrical fuse, 600V (UL), 32A, 200 kAIC at 300 Vdc, 50 kAIC at 300 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end, Class aR, White, Ceramic

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWC-32A10F
	UPC
	051712796484
EAN	Product Length/Depth
5027590420525	38 mm
Product Height	Product Width
11 mm	11 mm
Product Weight	Warranty
9.4 g	Not Applicable
Compliances	Certifications
CE Marked	CSA Certified
RoHS Compliant	UL Recognized

Product specifications

Interrupt rating

200 kAIC Vac

Release characteristic

Other

Amperage Rating

32 A

Frequency rating - max

62 Hz

Fuse type

FWC-A10F

Accessories

BMM Fuse block

CHM modular fuse holder

Fuse size

10 x 38 mm

Voltage rating

600 V

Fuse indicator

Other

Construction size

10 x 38 mm

Clearing (I2T)

600

Color

White

Connection

Ferrule end x ferrule end

Quantity

10

Material

Ceramic

Utilization category

aR (accompanied semiconductor protection)

Watt losses

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Compliance information

UKCA FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

CE FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

Technical data sheets

720011 FWC

7.5 W

Type

High speed fuse

Fuse shape

Cylindrical

Used with

Finger safe holders/blocks and striker

Breaking capacity

200 kA

Frequency rating - min

45 Hz

Class

Class aR

Pre arc (I2T)

95

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Voltage type

AC/DC

Packaging type

Standard



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)