



Datasheet 183-4223

RS PRO UNCOATED BALL-LOCK STAINLESS STEEL CABLE TIES

EN



Technical Information:

Material: Stainless Steel Grade 304

304 grade stainless steel, for standard applications

Working Temp.: -80°C to +500°C

Description: Metallic band and buckle

Flammability: Fireproof

Other Properties: UV-resistant

Product Feature: Uncoated version, for high temperature applications, quick installation.

Applications: Ideal for petrochemical, food industry, industries, power stations, mining, ship-building, offshore and any other aggressive environments.

Specification

| RS CODE | EASE CODE | LENGTH | | WIDTH | | TICKNESS | | MAX. BUNDLE DIAMETER | | MIN. TENSILE STRENGTH | |
|---------|------------------------|--------|------|-------|------|----------|-------|----------------------|------|-----------------------|-----|
| | | mm | inch | mm | inch | mm | inch | mm | inch | N | lbs |
| 1834223 | CT-SS-BL125/4.6UC-304 | 125 | 4.9 | 4.6 | 0.18 | 0.26 | 0.010 | 31 | 1.23 | 1100 | 250 |
| 1834224 | CT-SS-BL-200/4.6UC-304 | 200 | 7.9 | | | | | 50 | 1.97 | | |
| 1834225 | CT-SS-BL-360/4.6UC-304 | 360 | 14.2 | | | | | 90 | 3.55 | | |
| 1834226 | CT-SS-BL-360/7.9UC-304 | 360 | 14.2 | 7.9 | 0.31 | 0.26 | 0.010 | 90 | 3.55 | 1500 | 340 |

