

FEATURES

- Normal latch to catch fixing centre is 63.3 mm (max.)
- 70kgf maximum operating tension
- Suitable for screw fixing using 2 x M4 screws for latch and 2 x M5 screws for catch
- Padlockable versions
- Hand operated and easy to use toggle and fastener clamp
- Draw latch with over centre fastener

Stainless Steel, Lockable, Lock not included Latch

RS Stock No.: 197-4176



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

RS PRO robust general purpose toggle latch with a 4 mm wire link and the facility to padlock secure. These toggle latches have a length of 84 mm, width of 32 mm and depth of 17 mm. Toggle latches are a type of mechanical fastener and are also known as over centre fasteners, draw latches, and quick release fasteners and offer secure and easy fastening when locked. The unique cam action design makes the toggle latch strong and reliable and the quick release function means it can open quickly. When choosing a toggle latch you need to consider the maximum load to which it will be subject to as each latch and hook has been designed for a maximum load. RS PRO have a great range of stainless steel and steel toggle latches and door latches to suit large or small-scale applications including high strength latches, lockable, adjustable and non-adjustable options.

[186-1389](#) - Padlock hasp steel toggle latch

[197-4176](#) - Padlock hasp stainless steel toggle latch

General Specifications

Material	Stainless Steel
Lockable	Lock Not Included, Yes
Operating Tension	70kgf
Application	Cases and containers, Enclosures, Industrial machinery, food containers and marine equipment, light duty applications

Mechanical Specifications

Dimensions	84mm x 32mm x 17mm
Depth	17mm
Length	84mm
Width	32mm

Approvals

Compliance/Certifications 2011/65/EU and 2015/863



