



ENGLISH

Datasheet

**RS Pro Quick Acting F LBC fuse, 800mA 5 x 20mm BP**

RS Stock No: **563-655A**



## Product Details

RS Pro quick acting LBC fuse is current rated for 800 mA. This F-speed, glass bodied fuse is ideal for protection of electrical circuits and consumer appliances.

**Specifications:**

|   |   |
|---|---|
| Body Material                                 | Glass   |
| Breaking Capacity (at Maximum Voltage Rating) | 35 A  |
| Current Rating                                | 0.8 A   |
| Diameter                                      | 5.2 mm  |
| Fuse Speed                                    | F   |
| High Rupture Capacity                         | No  |
| Includes Indicator                            | No  |
| Maximum Operating Temperature                 | +125°C  |
| Minimum Operating Temperature                 | -55°C   |
| Operating Temperature Range                   | -55 to +125°C   |
| Overall Dimensions                            | 5.2 x 20 mm   |
| Overall Length                                | 20 mm   |
| Resistance                                    | 0.1265 $\Omega$   |
| Size Designation                              | Miniature   |
| Voltage Rating                                | 250 V ac  |
| Standards Met                                 | CSA Acceptance, UL Recognised, RoHS Compliant, VDE, BSI, CCC, KTL, SEMKO Approved |