



## Trailer Stabilizer Jacks

- A “must” for safely loading and unloading trailers !
- Meet OSHA Specification with our wide variety of Trailer Stabilizing Jacks OSHA 1910.178(k)(3) states “Fixed jacks may be necessary to support a semi-trailer and prevent upending during the loading or unloading when the trailer is not coupled to a tractor”.

Model	TJ50	TJ50A	TJ50B	TJ50C	TJ50D
Service Range (in.)	39- <sup>1</sup> / <sub>2</sub> -51	39-51	39-51	45-57	45-57
Static Capacity (lbs/ tonne)	100000/ 45	100000/ 45	100000/ 45	80000/ 36	100000/ 45
Lifting Capacity (lbs/ tonne)	40000/18	40000/18	50000/22.7	40000/18	40000/18
Cap Size	8”diameter	7.5”diameter	8”diameter	8”diameter	8”diameter
Net Weight (lbs/kg)	125/57	110/50	125/57	115/52	130/59



TJ50

Model	TJ60	TJ60A
Service Range (in.)	39- <sup>1</sup> / <sub>2</sub> -51	39- <sup>1</sup> / <sub>2</sub> -51
Static Capacity (lbs tonne)	100000/ 45	80000/ 36
Lifting Capacity (lbs/ tonne)	50000/22.7	40000/18
Beam Size	6”width x 24”length	6”width x 24”length
Net Weight (lbs/kg)	195/88.5	180/82



TJ60A