



## Main

Range	New Unica
Product or component type	USB charger + socket-outlet
Fixing mode	Clip-in

## Complementary

Device presentation	Mechanism
Type of USB power supply	USB type C
Device mounting	Flush
Number of modules	2 modules
Outlet poles configuration	2P + E
Outlet standard	French
Outlet standard description	Pin earth
Cover type	With shutter
Socket number	1
Rated current	10 A
Range compatibility	New Unica
Integrated connection type	1 USB port 5 V 2.1 A 50...60 Hz
Colour tint	White (RAL 9003)
Surface finish	Glossy
Surface treatment	Untreated centre plate
Type of packing	Flow-pack
Quantity per set	Set of 10
Ambient air temperature for storage	-5...50 °C
Ambient air temperature for operation	-5...50 °C
Relative humidity	0...95 %
Service life in cycles	10000 cycles
Connections - terminals	Screwless terminals
Number of terminals	3
Number of cables	2
Clamping connection capacity	2 x 2.5 mm <sup>2</sup> for rigid or flexible cable(s)
Material	PC (polycarbonate): casing
Wire stripping length	12 mm
Height	45 mm
Width	45 mm
Depth	41.2 mm
Embedding depth	29.3 mm
Net weight	0.045 kg
Standards	IEC 60884-1

## Environment

Product certifications	NF[RETURN]CE
IK degree of protection	IK04
IP degree of protection	IP20
Environmental characteristic	Oil UV resistant Acetone Liquid soap Window-cleaning fluid Petrol Alcohol Bleach

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>