

MIP12312

Enclosure, Resi9 MP, surface mounting, 3 rows of 12 modules, IP40, white door, 1 earth + 1 neutral terminal blocks



Main

| | |
|-----------------------------|-------------------|
| Range | Resi9 |
| Product name | Resi9 MP |
| Product or component type | Enclosure |
| Enclosure type | Modular enclosure |
| Nb of 18 mm modules per row | 12 |
| Nb of horizontal rows | 3 |
| Type of door | Plain |
| Width | 268 mm outside: |
| Height | 478 mm outside: |
| Depth | 102 mm outside: |

Complementary

| | |
|-------------------------------|--|
| Enclosure mounting | Surface |
| 9 mm pitches | 24 |
| Total number of 18 mm modules | 36 |
| [In] rated current | 63 A |
| Type of rail | 35 mm asymmetrical rail |
| Mounting plate description | Without mounting plate |
| Cable entry | 1 trunking flange 1 bare flange |
| Terminal block function | Earth / neutral |
| Number of terminal blocks | 1 earth (screwed) with 20 outgoing 1 neutral (screwed) with 20 outgoing |
| Distribution block outgoing | 2 x 16 mm ² for earth 2 x 16 mm ² for neutral 9 x 10 mm ² for earth 9 x 10 mm ² for neutral 9 x 6 mm ² for earth 9 x 6 mm ² for neutral |
| Enclosure material | Back part: technoplastic Door: technoplastic Front face: technoplastic |
| Internal depth | 80 mm |
| Colour | Door: white (RAL 9003) Front face: white (RAL 9003) |
| Market segment | Small commercial Residential |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

| | |
|---------------------------------------|---|
| Standards | IEC 61439-1 IEC 61439-3 IEC 60670-1 IEC 60670-24 |
| Quality labels | IMQ |
| Fire resistance | Door: 650 °C Back part: 650 °C Front face: 650 °C |
| IP degree of protection | IP40 |
| IK degree of protection | IK07 |
| Ambient air temperature for operation | -25...60 °C |

Packing Units

| | |
|------------------------------|------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 11.400 cm |
| Package 1 Width | 27.100 cm |
| Package 1 Length | 47.900 cm |
| Package 1 Weight | 1.602 kg |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 4 |
| Package 2 Height | 32.000 cm |
| Package 2 Width | 42.100 cm |
| Package 2 Length | 53.600 cm |
| Package 2 Weight | 6.892 kg |
| Unit Type of Package 3 | P12 |
| Number of Units in Package 3 | 64 |
| Package 3 Height | 120.000 cm |
| Package 3 Width | 80.000 cm |
| Package 3 Length | 120.000 cm |
| Package 3 Weight | 122.272 kg |

Offer Sustainability

| | |
|-----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Halogen content performance | Halogen free product |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|