

Datasheet

RS Pro Stud Terminal, 17170.2 series, 1000 V (IEC), 1000 V (UL), 600 V (CSA), 115 A (UL), 125 A (IEC), 130 A (CSA)

RS Stock No: **872-4824**



Product Details

RS Pro stud terminal in beige colour, has 600 V (CSA), 1000 V (IEC), 1000 V (UL) voltage rating and 115 A (UL), 125 A (IEC), 130 A (CSA) current rating. The housing is made from nylon 66 for durability. This double level stud terminal foot can be snapped on TS 35 DIN rail.

Features and Benefits

- Foot can be snapped on TS 35 DIN rail
- Single stud connection
- Nylon 66 housing UL 94-V0

**Specifications:**

Colour	Beige
Current Rating	130 A (CSA), 125 A (IEC), 115 A (UL)
Maximum Operating Temperature	+120°C
Minimum Operating Temperature	-40°C
Number of Levels	Double
Termination Method	Stud
Voltage Rating	600 V (CSA), 1000 V (IEC), 1000 V (UL)
Wire Size	14 to 2 AWG
Clamping Area	2.5 to 50 mm ²
Material	Nylon 66
Rated Impulse Voltage	8 kV
Screw Size	M6
Standards Met	UL 94V-0, CSA, IEC