

Datasheet

ENGLISH


RS PRO, 12 V dc, 3000 gcm, Brushed DC Geared Motor, Output Speed 153 rpm

Stock No: 834-7657



Specifications:

Output Speed	153 rpm
Supply Voltage	12 V dc
Maximum Output Torque	3000 g.cm
DC Motor Type	Brushed
Shaft Diameter	6mm
Power Rating	7 W
Gearhead Type	Spur
Length	73.7mm
Width	37mm
Current Rating	840 mA
Weight	214g



Operating relative humidity 20% ~ 85%
 Operating temperature range -10°C ~ +60°C

Ratio	L
47:1	27.1mm

Gearbox Housing material	Metal
Backlash at no-load	< 2°
Bearing at output	Sleeve bearings
Radial load (10mm from flange)	< 1 kgf
Shaft axial load	< 0.7 kgf
Shaft press fit force max	< 5 kgf
Radial play of shaft	< 0.05mm
Thrust play of shaft	< 0.35mm

Reduction Ratio	Rated tolerance Torque	Max momentary Tolerance Torque	Efficiency
1/47	3.0 kgf-cm Max.	9.0 kgf-cm	66%

Reduction Table RPM SUPPLY VOLTAGE	4.5v	6v	9v	12v
834-7657	47	77	115	153

Note: Motor speeds may vary by (+) or (-) 12.5%

