

SBP20KRMI4U

APC Service Bypass Panel, 230V, 125A, 2x hardwire input connectors, 8x IEC 60320 C19 outlets



Overview

Lead time Usually in Stock



Main

Main Input Voltage	220 V 230 V 240 V 380 V 3 phases 400 V 3 phases 415 V 3 phases
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Number of rack unit	4U
Number of cables	1
Provided equipment	Installation guide Rack mounting brackets User manual

Physical

Colour	Black
Height	17.8 cm
Width	43.2 cm
Depth	57.2 cm
Net weight	18.78 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted

Input

Network frequency	50/60 Hz
Number of input connectors	1 hard wire 3-wire (1P + N + E) 1 hard wire 5 wire (3P + N + E)
Max line current	125 A
Input current limits	125 A
Load capacity	20000 VA
Power factor	0...1

Output

Max current draw	125 A
Number of power socket outlets	8 IEC 60320 C19
Protection type	Circuit breaker
Efficiency	99 %

Conformance

Product certifications	CSA[RETURN]GOST
------------------------	-----------------

Environmental

Ambient air temperature for operation	-20...50 °C
Relative humidity	0...95 %
Operating altitude	0...15000 ft
Ambient air temperature for storage	-40...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	30.5 cm
Package 1 Width	84.3 cm
Package 1 Length	61 cm
Package 1 Weight	31.36 kg

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	2 years (parts only)
----------	----------------------