



### Overview

Lead time	Usually in Stock
-----------	------------------

### Main

PDU type	Basic
Cable length	3.05 m
Number of cables	1
Provided equipment	Installation guide Safety guide

### Complementary

Main Input Voltage	230 V
Height	162.6 cm
Width	5.6 cm
Main Output Voltage	230 V
Depth	4.3 cm
Net weight	6.18 kg
Mounting location	Side
Mounting preference	No preference
Input Connection Type	IEC 60309 32 A 2P + E
Mounting mode	Not rack-mountable
Number of rack unit	0U
Mounting position	Vertical
Permissible voltage	200...240 V
Input current limits	32 A
Load capacity	7400 VA
Network frequency	50/60 Hz
Number of power socket outlets	20 IEC 60320 C13 6 IEC 60320 C19

### Environment

Product certifications	CE[RETURN]EAC[RETURN]IRAM[RETURN]VDE
Ambient air temperature for operation	0...50 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...65 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Storage Relative Humidity	5...95 %
Storage altitude	0.00...15240.00 m

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	187.5 cm
Package 1 Width	13.5 cm
Package 1 Length	22.6 cm
Package 1 Weight	8 kg

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Lead free	Yes
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

### Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------