

FEATURES

- Material: Warp proof self-extinguishing UL approved PVC, 94V-0 flammability rating, M1 rating NF fire resistant test.
- Color: Black
- These devices are for routing of wires within devices in factory installations.
- Features parallel holes on both sidewalls to facilitate cutting in wire application.
- Special color, size, length upon request of reasonable quantity.

RS PRO Wiring Duct

RS Stock No.: 2339189



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description ATTRIBUTE 1

- Material: Warp proof self-extinguishing UL approved PVC, 94V-0 flammability rating, M1 rating NF fire resistant test.
- Color: Black
- Vicat softening point: 86°C
- UL Test up to 50°C
- These devices are for routing of wires within devices in factory installations.
- Features parallel holes on both sidewalls to facilitate cutting in wire application.
- Special color, size, length upon request of reasonable quantity.
 - Regular wiring duct cover can be upgrade to NON-SLIP ones which improves tightness between duct and cover, benefits vertical installations, and improves effectiveness and avoid cover slip off.

General Specifications

| | |
|--------------------------------------|---|
| Series | Wiring Duct |
| Type | |
| Colour | Black |
| Material | PVC |
| UV Resistant | NO |
| Minimum Operating Temperature | 0°C |
| Maximum Operating Temperature | Vicat softening point: 86°C, UL Test up to 50°C |
| Fire Behaviour | Self-Extinguishing |
| Quantity | 2M |

Mechanical Specifications

| | |
|---|---------------|
| Length | 200cm(2M) |
| Width X High | 80 x 60 mm |
| Slot | 8mm |
| Wires to be Contained(16-14 AWG) | 180 ~ 210 pcs |

Approvals

| | |
|----------------------|-----------|
| Declarations | |
| Standards Met | CSA, RoHS |

Similar Products

| Stock No. | Brand | Product Name | Colour | Material |
|-----------|-------|--------------|--------|----------|
| 301-2084 | | | Black | PVC |



Unit:mm

| W x H (mm) | Slot | Wires to be Contained (16-14 AWG) | Length | Color |
|------------|------|-----------------------------------|--------|-------|
| 80x60 | 8 | 180 ~ 210 pcs | 2M | Black |

