

FEATURES

- Material: UL approved Nylon 66, 94V-2
- Color: Grey (RAL7035)available in other colors.
- Suit a variety of applications, and diverse industries.
- Function :Mount gland to pre-drilled panel hole, use locknut to fix gland on board, insert the cables in the seal,and then tighten up the nut to hold cables in position.
- Simply and quickly fixed, high degree of the protection IP68 preventing dust and water.

RS PRO Cable Gland

RS Stock No.: 214-1080



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.



PR0

- Material: UL approved Nylon 66, 94V-2
- Color: Grey(RAL7035), available in other colors.
- Suit a variety of applications, and diverse industries.
- Function : Mount gland to pre-drilled panel hole, use locknut to fix gland on board, insert the cables in the seal, and then tighten up the nut to hold cables in position.
- Feature : Simply and quickly fixed, high degree of the protection IP68 preventing dust and water.
- Available to order the accessories separately. Follow the drawing and add the letter to the suffix part number, L for locknut, W for washer, B for gland body, S for seal, N for nut.

General Specifications

Cariaa	Matria Thusad				
Series	Metric Thread				
Туре	Cable Gland				
Colour	Grey(RAL7035)				
Material	Nylon 66				
Finish					
Application					
Resistant To					
UV Resistant	No				
Minimum Operating Temperature	-40°C				
Maximum Operating Temperature	85°C				
Fire Behaviour	Self-Extinguishing				
Quantity	5рс				

Mechanical Specifications	
Thread	M25/40/32/63 x P1.5
Mounting Hole	
Cable Range	

Protection Category	
IP Rating	IP68 (only if the locknut and washer are assembled)



Approvals

Declarations	
Standards Met	UL, RoHS, CE, HF

Similar Products



RS Article(will be replayed RS new article no.)		Mounting Hole	D1	D2	B1	L1	L2	L3	Cable Range	Packing
2141080	M63xP1.5	63.0~63.4	63	55	42	17	46	34	32 ~ 42	5PCS

** IP68 (only if the locknut and washer are assembled)

