TECHNICAL DATA SHEET

Packing

Temperature range



RoHS

Compliant

Speaker Cable Model: CBBR0949

Design of cable: Inner conductor 13/0.17±0.004mm(Strand Copper) Ø0.7±0.1mm PVC Jacket Colour White with black trip Size Ø2.2X4.4±0.2mm Wall thickness ≈0.7mm Printing By request Electric data at 20°C <66Ω/km Conductor resistance Insulation resistance >200MΩ*km Testing voltage wire/wire 50Hz1min=800V

100m on non returnable reels

 $-10^{\circ}C \sim 60^{\circ}C$

Important Notice : This data sheet and its contents (the "Information") belong to pro-POWER. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but pro-POWER assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where pro-POWER was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict pro-POWER's liability for death or personal injury resulting from its negligence.

