

## Features

- Made from solid nitrile rubber
- Can be stretched without requiring unit disassembly
- Accommodates considerable axial misalignment
- Seals effectively on oval shafts
- Wide tolerance of shaft sizes

## RS PRO Seals-V-Ring Seals

RS Stock No.: see below



RS PRO Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

## Product Description

The RS PRO V-Ring is an all-rubber seal designed for rotary shafts. Mounting directly onto the shaft, the elastic body holds itself firmly on the rotating shaft while the lip seals axially against the counter face, bearing race, bore housing or similar surfaces.

## Similar Products

Stock no.	Reference	Shaft Dia. C (mm)	Outside Dia. of Seal (mm)	Seal dia. d1 (mm)	Profile height W (mm)	Profile Width B2 (mm)	Total Width B (mm)	Max. Permissible d2 (mm)	Min. Permissible d3 (mm)	Fitted Width B1 (mm)
749575	V6A	5.5 - 6.5	9.5 - 10.5	5	2	2.4	3.7	C + 1	C + 6	3.0 ± 0.4
749581	V10A	9.5 - 11.5	15.5 - 17.5	9	3	3.4	5.5	C + 2	C + 9	4.5 ± 0.6
749597	V12A	11.5 - 12.5	17.5 - 18.5	10.5	3	3.4	5.5	C + 2	C + 9	4.5 ± 0.6
749604	V14A	13.5 - 15.5	18.5 - 21.5	12.5	3	3.4	5.5	C + 2	C + 9	4.5 ± 0.6
749610	V16A	15.5 - 17.5	21.5 - 23.5	14	3	3.4	5.5	C + 2	C + 9	4.5 ± 0.6
749626	V20A	19 - 21	27 - 29	18	4	4.7	7.5	C + 2	C + 12	6.0 ± 0.8
749632	V22A	21 - 24	29 - 32	20	4	4.7	7.5	C + 2	C + 12	6.0 ± 0.8
749648	V25A	24 - 27	32 - 35	22	4	4.7	7.5	C + 2	C + 12	6.0 ± 0.8
749654	V30A	29 - 31	37 - 39	27	4	4.7	7.5	C + 3	C + 12	6.0 ± 0.8
749660	V35A	33 - 36	41 - 44	31	4	4.7	7.5	C + 3	C + 12	6.0 ± 0.8
749676	V40A	38 - 43	48 - 53	36	5	5.5	9	C + 3	C + 15	7.0 ± 1.0
749682	V45A	43 - 48	53 - 58	40	5	5.5	9	C + 3	C + 15	7.0 ± 1.0
749698	V50A	48 - 53	58 - 63	45	5	5.5	9	C + 3	C + 15	7.0 ± 1.0

