


## **MSA Compliant QSFP+ Direct-Attach Twinax Breakout Cable - 2 m (6.6 ft)**

Product ID: QSFP4SFPPC2M



The QSFP4SFPPC2M is an MSA Compliant QSFP+ direct-attach Twinax breakout cable. It is designed, programmed and tested to bridge 40G network equipment with 10G compatible servers or routers. This passive Twin axial cable connects a single QSFP+ port to four 10G SFP+ ports and is fully hot-pluggable making upgrades and replacements seamless by minimizing network disruptions.

At 2 meters long and designed for short-length, high-speed interconnects, this low-power, low-latency copper QSFP+ cable also uses a cost-effective cabling alternative to fiber-optic assemblies. It supports short-distance applications such as point-to-point in-rack and across-rack network switch or server connections, for up to four 10G SFP+ devices.

### **StarTech.com SFP Cables**

All StarTech.com QSFP & QSFP+ cables are backed by a lifetime warranty and free lifetime multilingual technical support. StarTech.com offers a wide variety of direct-attach SFP Cables and SFP modules, providing the convenience and reliability you need to ensure dependable network performance.

### Certifications, Reports and Compatibility



### Applications

- Use in 40Gb/10Gb mixed Ethernet network applications
- Point-to-point in-rack server or network switch connections, for up to four devices

### Features

- Delivers reliable copper 40 GbE Ethernet connections
- StarTech.com SFP cables are backed by a lifetime warranty
- Uses a cost-effective cabling alternative to fiber-optic setups
- Complies with Multi-Source Agreement (MSA) industry standards
- Low power consumption of less than 1 W
- Hot-swappable

<b>Hardware</b>	Warranty	Lifetime
	Cable Type	Passive Copper Cable
	Compatible Brand	MSA Compliant
<b>Performance</b>	Compatible Networks	40 Gbps
	Maximum Data Transfer Rate	40Gbps for QSFP+ / 10Gbps for SFP+
<b>Connector(s)</b>	Connector A	1 - QSFP+ Latching Plug
	Connector B	4 - SFP+ Latching Plug
<b>Power</b>	Power Consumption (In Watts)	< 0.1 W (per end)
<b>Environmental</b>	Operating Temperature	0°C to 70°C (32°F to 158°F)
	Storage Temperature	-40°C to 80°C (-40°F to 158°F)
<b>Physical Characteristics</b>	Cable Length	6.6 ft [2 m]
	Color	Black
	Product Height	0.5 in [1.2 cm]
	Product Length	6.6 ft [2 m]
	Product Width	0.6 in [14 mm]
	Weight of Product	12.2 oz [346 g]
<b>Packaging Information</b>	Package Height	1.2 in [30 mm]
	Package Length	12.8 in [32.5 cm]
	Package Width	9.8 in [25 cm]
	Shipping (Package) Weight	12.8 oz [364 g]
<b>What's in the Box</b>	Included in Package	1 - QSFP+ to 4x SFP+ cable
	Cable Jacket Type	PVC - Polyvinyl Chloride
	Impedance	100 Ohm
	Wire Gauge	30 AWG

Product appearance and specifications are subject to change without notice.