

Product data sheet

Characteristics

SRTL5KRM2UI

APC Smart-UPS Ultra On-Line, 5000VA, Lithium-ion, Rack/Tower 2U, 230V, 6 C13 + 4 C19 IEC outlets, Network Card, Extended runtime, W/rail kit



Overview

Lead time Usually in Stock



Main

Main Input Voltage	230 V
Product or component type	Uninterruptible power supply (UPS)
Other Input Voltage	220 V
Main Output Voltage	230 V
Other Output Voltage	220 V
Rated power in W	5000 W
Rated power in VA	5000 VA
Output connection type	6 IEC 60320 C13 4 IEC 60320 C19
Number of rack unit	2U
Number of cables	1
Battery type	Li-Ion (Lithium-Ion)
Provided equipment	1 CD (software and documentation) USB cable Front cover Earth terminal block Temperature sensor Stabilization feet Rail extension 2P-3P connector

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	1.5 h
Number of battery replacement quantity	1
Battery voltage	180 V
Battery charger power	600 W rated
Battery life	5...10 year(s)
Extended runtime	1

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

General

Product web sub-family	High density
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Colour	Silver grey
Height	86 mm
Width	432 mm
Depth	701 mm
Net weight	29.2 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Rack-mounted Tower-mounted with kit
Two post mountable	0
USB compatible	No
Mounting position	Horizontal Vertical

Input

Network frequency	40...70 Hz auto-sensing
Number of input connectors	1 hard wire 3-wire (1P + N + E)
Input voltage limits	180...275 V adjustable (half load)

Output

Maximum configurable power in W	5000 W
Harmonic distortion	Less than 2 %
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Crest factor	3 : 1
UPS type	Double conversion online
Wave type	Sine wave
Bypass type	Internal bypass (automatic and manual)
Full load runtime	00:05:00 5000 W
Half load runtime	00:12:00 2500 W
Maximum configurable power in VA	5000 VA

Conformance

Product certifications	CE[RETURN]UKCA[RETURN]EN/IEC 62040-1
Marking	CE Mark UKCA

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0.00...15240.00 m
Acoustic level	55 dBA
Heat dissipation	931 Btu/h
IP degree of protection	IP20

Communications & Management

Free slots	0
Alarm	Audible and visible alarms : prioritized by severity
Emergency power off	Yes

Surge Protection and Filtering

Surge energy rate	1260 J
-------------------	--------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	4
Package 1 Height	39.2 cm
Package 1 Width	58.5 cm
Package 1 Length	98.4 cm
Package 1 Weight	38.5 kg
SCC14	10731304435754

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	5 years
----------	---------