



Main

| | |
|---------------------------|---|
| Product or component type | USB charger |
| Integrated connection | 2 USB type A 5 V DC, maximum load current: 2.1 A type |

Complementary

| | |
|---|---|
| Device mounting | Flush |
| Device presentation | Complete product |
| Colour tint | Metal gold hairline |
| Surface finish | Glossy |
| [Ue] rated operational voltage | 100/240 V AC 50/60 Hz |
| Maximum load current with 2 outputs used simultaneously | 2.1 A |
| Material | PC (polycarbonate) |
| Connections - terminals | Screw terminals |
| Screwdriver shape | Phillips combined |
| Clamping connection capacity | 1.5...2.5 mm ² for flexible cable(s) 1.5...2.5 mm ² for rigid cable(s) |
| Height | 86 mm |
| Width | 86 mm |
| Depth | 40 mm |

Environment

| | |
|-----------------------------|-------------|
| Standards | IEC 60950-1 |
| Electrical insulation class | Class II |
| IP degree of protection | IP20 |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 3.4 cm |
| Package 1 Width | 8.6 cm |
| Package 1 Length | 8.6 cm |
| Package 1 Weight | 104.0 g |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 8 |
| Package 2 Height | 9.5 cm |
| Package 2 Width | 19.0 cm |

| | |
|------------------|---------|
| Package 2 Length | 19.5 cm |
| Package 2 Weight | 882.0 g |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations Circularity Profile |