

FEATURES

- 316L Stainless steel
- Manufactured to ISO9001:2008, RoHS, CE
- Withstands corrosive environments to aggressive fluid
- Can be used with food, medical and chemical applications
- Can be used in extreme hot or cold conditions

RS PRO Push-In Fittings Male Stud Coupling

RS Stock No.: 2351278



Product Description

Part No.	Tube OD	Thread
2351278	6 mm	1/8" NPT



Features

- 316L Stainless steel
- Manufactured to ISO9001:2008, RoHS, CE
- Withstands corrosive environments to aggressive fluid
- Can be used with food, medical and chemical applications
- Can be used in extreme hot or cold conditions

General Specifications

Working pressure	0 to 5 bar (0 to 225 psi)	
Working temperature	-15°C to +220°C	
Vacuum rating	To 28" Hg	
Working medium	Air, water, oil	
Recommended tubing	PTFE, FEP, PU, PE, PA, PVDF	

	7	4 -	ria	п-
- 17	11-1	ТΩ		ľ

Body	Stainless steel 316L
Release sleeve	Stainless steel 316L
Collar / lock claw	Stainless steel 316L
V-seals / o-rings	FKM

Similar Products

Part No.	Tube OD	Thread
2351279	8 mm	1/4" NPT