

Features

- Galvanised steel wire outer covering
- High tensile steel wire reinforcing
- Suitable for mineral oils, lubricating oils, water glycol, water-oil emulsion hydraulic fluids

RS PRO Hydraulic Hose Assemblies

RS Stock No.: 110-2248



RS PRO Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

RS PRO hydraulic hose assembly of 500 mm, has maximum operating pressure of 155 bar. It has galvanised steel wire outer covering and high tensile steel wire reinforcing for durability. The hose assembly features straight G 3/8 female connector on both ends. It has operating temperature range of -40 to +121°C and is suitable for mineral oils, lubricating oils, water glycol and water-oil emulsion hydraulic fluids applications.

General Specifications

Connector A - Angle	Straight
Connector A - Gender	Female
Connector A - Thread Size	3/8 in
Connector A - Thread Standard	G
Connector A	Straight G 3/8 Female
Connector B - Angle	Straight
Connector B - Gender	Female
Connector B - Thread Size	3/8 in
Connector B - Thread Standard	G
Connector B	Straight G 3/8 Female
Cover Material	Galvanised Steel Wire
Inner Hose Material	Synthetic Rubber
Maximum Operating Pressure	155 bar
Maximum Operating Temperature	+121°C
Minimum Operating Temperature	-40°C
Reinforcing Material	Steel

Mechanical Specifications

Inside Diameter	3/8 in
Overall Length	500 mm

Approvals

Standards Met	RoHS Compliant
---------------	----------------