




PART NO.

DSI-EV32S-NC

REVISIONS								
ECN#	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
-	1.0	RELEASED	AB	18/04/12	ER	18/04/12	ER	18/04/12







Features

Hinged Lid

· Low Contact Resistance



Specification

Current and Voltage : 32A 240V AC Signal Current : 2A < 30V DV

Protection Degree : IP44

Charging Cable : 32A 1P + N + PE + PP + CP

: 3,000mm / 5,000mm 3 × 6mm² + 2 - 0.5mm² Charging Cable The plug II, was designed according to the standard of 62196-2 IEC

2010 sheet 2-IIb

Cable Specification

Function	32A 240V			
L1 (1)	6mm²			
N (2)	6mm²			
PE (3)	6mm²			
CP (4)	0.5mm ²			
PP (5)	-			

Part Number Table

Description	Part Number		
Socket EV J1772 32A	DSI-EV32S-NC		

www.element14.com www.farnell.com www.newark.com

Dimensions: Millimetres (Inches)

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of its other the for information supremosal increased in the three dates the which it subjects. No license for the properties of several properties of several properties of several properties.	TOLERANCES:
other than for information purposes in connection with the products to which it relates. No licence of an ellectual properly rights is granted. The Information is subject to change without notice and replaces at the sheets previously supplied. The Information supplied is believed to be accurate but the Group assume responsibility for its accuracy or completeness, any error in or omission from it or for any use made or Users of this data sheet should check for themselves the Information and the suitability of the product their purpose and not make any assumptions based on information included or omitted. Liability for los damage resulting from any reliance on the Information or use of it (including liability resulting from negli one or where the Group was aware of the possibility of such loss or damage arising) is excluded. This wit to perate to limit or restrict the Group's liability for death or personal injury resulting from its negligence ulticome is the resistered trademark of the Group. @ Premier Farnell lot 2012.	UNLESS OTHER SPECIFIED, DIMENSIONS AI FOR REFERENC PURPOSES ONI

f	TOLENANCES.
1	
	UNLESS OTHERWISE
f	SPECIFIED,
	DIMENSIONS ARE
i	FOR REFERENCE
	PURPOSES ONLY.

	DRAWN BY:	DATE:	
	AB	18/04/12	
	CHECKED BY:	DATE:	
	ER	18/04/12	
	APPROVED BY:	DATE:	
	ER	18/04/12	

:	DRAWING TITLE:						
12	Socket EV J1772 32A						
<u>:</u> :	SIZE	SIZE DWG NO.			ELECTRONIC FILE		
12	A4	DSI-EV32S-NC-01		DSI-EV32S-NC-1		1.0	
:	SCALE: NTS		U.O.M.: mı	m (inch)	SHEET: 1 of 1		