

#### **FEATURES**

- 3W LED PCB
- 3-hour minimum emergency duration
- Includes legend kit additional legends available separately
- Ni-Cad rechargeable battery
- Impact resistant polycarbonate diffuser and base on the bulkhead
- Painted steel body with polycarbonate screen on exit box
- Can be wired for maintained or nonmaintained operation
- Constant light output
- IP65

# LED Emergency Lighting Bulkhead 3 W

RS Stock No.: 795-9378



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

# **Emergency Lighting**



#### **Product Description**

This LED emergency bulkhead offers an energy saving and cost effective solution to fulfil emergency lighting requirements. The bulkhead is wired as maintained, but it can also be wired as non-maintained if required.

## **General Specifications**

Lamp Type	3W LED
Light Style	Bulkhead
Luminosity	120lm
Colour Temperature	3500K
Maintained	Maintained
Material	Polycarbonate
Duration	3h Min.
Lamp Supplied	Yes
Applications	LED emergency exit signs are ideal for commercial, industrial and retail applications and can be found in: Corridors, Workshops, Emergency exits

### **Electrical Specifications**

Wattage	3W
Voltage Rating	230V
Battery	NiCD 1.5Ah 3.6V

# **Emergency Lighting**



## **Mechanical Specifications**

Length	350mm
Width	117mm
Depth	76mm
Fitting Type	Bulkhead

## **Spacing Tables**

1lux Minimum at Centre				
Mounting Height	Transverse to wall	Transverse to transverse	Axial to wall	Axial to Axial
2.5m	3.3	6.6	2.2	4.35
4.0m	4	8	2.3	4.55

Open (anti-panic) Area – 0.5lux minimum				
Mounting Height	Transverse to wall	Transverse to transverse	Axial to wall	Axial to Axial
2.5m	3.25	6.5	2.45	4.9
4.0m	3.6	7.2	3	6
6.0m	3.7	7.4	3.1	6.15

## **Protection Category**

IP Rating	IP65
-----------	------

## **Approvals**

Standards Mets	BS EN 60598-1 , BS EN 60598-2-22 , BS EN 55015 , BS EN 61547 , BS EN 61000-3-2, BS EN 61000-3-3
EU Energy Efficiency Rating	A+



## **Emergency Lighting**



Maintained(3M)

- + on/off Switched
- + Emergency (remove link)



Maintained(3M)

- + Light on 24/7
- + Emergency (keep link)



Non-Maintained(3NM) + Light off 24/7

+ Emergency (remove link)

