

## FEATURES

- Abrasion, ozone and weather resistant
- Smooth rubber NBR / SBR construction
- In accordance with EN ISO 2398
- Wide temperature range -40°C to +90°C
- Safety factor 3:1

## RS PRO Air Hose Black NBR, SBR 17mm x 25m

RS Stock No.: 914-5525



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

### Product Description

Brought to you by RS Pro, a range of rubber air hoses, manufactured from a textile reinforced NBR/SBR synthetic rubber. Being Weather and ozone resistant, it is suitable for medium duty applications such as pneumatic air tools and compressors used in the construction and automotive industry and general workshop use. All models are highly reliable and excellent quality.

### General Specifications

<b>Colour</b>	Black
<b>Material</b>	NBR, SBR
<b>Number Of Tubes</b>	1
<b>Application</b>	Compressed Air Tools

### Mechanical Specifications

<b>Hose Inside Diameter</b>	10mm
<b>Hose Outside Diameter</b>	17mm
<b>Length</b>	25m
<b>Weight Per Metre</b>	0.29kg
<b>Bend Radius</b>	100mm

### Operation Environment Specifications

<b>Maximum Operating Pressure</b>	20 bar
<b>Minimum Operating Temperature</b>	-40°C
<b>Maximum Operating Temperature</b>	+90°C
<b>Burst Pressure</b>	60 bar

## Approvals

Compliance/Certifications

EN ISO 2398



RS Stock Number	Internal Diameter	External Diameter	Length	Weight per Meter	Max Working Pressure	Burst Pressure	Bend Radius
9145540	6 mm	12 mm	25 m	0.18 kg	20 bar	60 bar	60 mm
9145543	8 mm	15 mm	25 m	0.23 kg	20 bar	60 bar	80 mm
9145525	10 mm	17 mm	25 m	0.29 kg	20 bar	60 bar	100 mm
9145534	13 mm	21 mm	25 m	0.43 kg	20 bar	60 bar	130 mm
9145537	19 mm	29 mm	25 m	0.7 kg	20 bar	60 bar	190 mm
9145531	25 mm	36 mm	25 m	1.0 kg	20 bar	60 bar	250 mm