

Product data sheet

Characteristics

EPDU1216M

APC Easy Rack PDU, Metered, 0U, 3 Phase, 11kW, 230V, 16A, 21 x C13 and 3 x C19 outlets, IEC60309 3P+N+PE inlet



Overview

Lead time	Usually in Stock
-----------	------------------



Main

Colour	Black
PDU type	Metered
Cable length	1.98 m
Number of cables	1
Provided equipment	Installation guide Toolless mounting kit Vertical mounting brackets

Complementary

Main Input Voltage	400 V 3 phases
Height	117.5 cm
Width	6.2 cm
Main Output Voltage	230 V
Depth	4.44 cm
Net weight	2.74 kg
Mounting location	Side
Mounting preference	No preference
Input Connection Type	IEC 60309 16 A 3P + N + PE
Mounting mode	Rack-mounted
Number of rack unit	0U
Mounting position	Vertical
Input current limits	16 A
Load capacity	11000 VA
Network frequency	50/60 Hz
Number of power socket outlets	21 IEC 60320 C13 3 IEC 60320 C19

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Product certifications	CE[RETURN]EAC[RETURN]RCM[RETURN]TÜV
Ambient air temperature for operation	-5...45 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-20...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.00...4572.00 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	132 cm
Package 1 Width	11 cm
Package 1 Length	16 cm
Package 1 Weight	3.26 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------