












## RS Pro 22mm IP67 Circular Connectors

### No. of Contacts: 6 + PE

<p style="text-align: center;"><b>External-threaded Panel-Mount</b></p> <p style="text-align: center;">Stock No: <b>210-7311</b></p> 	Can mate with	<p style="text-align: center;"><b>Internal-threaded Standard Cable-Mount</b></p>  <table style="width: 100%; margin-top: 5px;"> <tr> <td style="text-align: right;">Stock No:</td> <td style="text-align: left;">Cable dia.</td> </tr> <tr> <td style="text-align: right;"><b>210-7325</b></td> <td style="text-align: left;">6.5mm</td> </tr> <tr> <td style="text-align: right;"><b>210-7326</b></td> <td style="text-align: left;">8.5mm</td> </tr> <tr> <td style="text-align: right;"><b>210-7327</b></td> <td style="text-align: left;">10.5mm</td> </tr> </table>	Stock No:	Cable dia.	<b>210-7325</b>	6.5mm	<b>210-7326</b>	8.5mm	<b>210-7327</b>	10.5mm	For in-line connection can mate with	<p style="text-align: center;"><b>External-threaded Standard Cable-Mount</b></p>  <table style="width: 100%; margin-top: 5px;"> <tr> <td style="text-align: right;">Stock No:</td> <td style="text-align: left;">Cable dia.</td> </tr> <tr> <td style="text-align: right;"><b>210-7304</b></td> <td style="text-align: left;">6.5mm</td> </tr> <tr> <td style="text-align: right;"><b>210-7305</b></td> <td style="text-align: left;">8.5mm</td> </tr> <tr> <td style="text-align: right;"><b>210-7306</b></td> <td style="text-align: left;">10.5mm</td> </tr> </table>	Stock No:	Cable dia.	<b>210-7304</b>	6.5mm	<b>210-7305</b>	8.5mm	<b>210-7306</b>	10.5mm	Can mate with	<p style="text-align: center;"><b>Internal-threaded Panel-Mount</b></p> <p style="text-align: center;">Stock No: <b>210-7324</b></p> 
Stock No:	Cable dia.																					
<b>210-7325</b>	6.5mm																					
<b>210-7326</b>	8.5mm																					
<b>210-7327</b>	10.5mm																					
Stock No:	Cable dia.																					
<b>210-7304</b>	6.5mm																					
<b>210-7305</b>	8.5mm																					
<b>210-7306</b>	10.5mm																					
		<p style="text-align: center;"><b>Internal-threaded Short Cable-Mount</b></p>  <table style="width: 100%; margin-top: 5px;"> <tr> <td style="text-align: right;">Stock No:</td> <td style="text-align: left;">Cable dia.</td> </tr> <tr> <td style="text-align: right;"><b>210-7320</b></td> <td style="text-align: left;">4.5-7 mm</td> </tr> <tr> <td style="text-align: right;"><b>210-7321</b></td> <td style="text-align: left;">7-12 mm</td> </tr> </table>	Stock No:	Cable dia.	<b>210-7320</b>	4.5-7 mm	<b>210-7321</b>	7-12 mm		<p style="text-align: center;"><b>External-threaded Short Cable-Mount</b></p>  <table style="width: 100%; margin-top: 5px;"> <tr> <td style="text-align: right;">Stock No:</td> <td style="text-align: left;">Cable dia.</td> </tr> <tr> <td style="text-align: right;"><b>210-7307</b></td> <td style="text-align: left;">4.5-7 mm</td> </tr> <tr> <td style="text-align: right;"><b>210-7308</b></td> <td style="text-align: left;">7-12 mm</td> </tr> </table>	Stock No:	Cable dia.	<b>210-7307</b>	4.5-7 mm	<b>210-7308</b>	7-12 mm						
Stock No:	Cable dia.																					
<b>210-7320</b>	4.5-7 mm																					
<b>210-7321</b>	7-12 mm																					
Stock No:	Cable dia.																					
<b>210-7307</b>	4.5-7 mm																					
<b>210-7308</b>	7-12 mm																					
		<p style="text-align: center;"><b>Internal-threaded 90° Cable-Mount</b></p>  <table style="width: 100%; margin-top: 5px;"> <tr> <td style="text-align: right;">Stock No:</td> <td style="text-align: left;">Cable dia.</td> </tr> <tr> <td style="text-align: right;"><b>210-7322</b></td> <td style="text-align: left;">4.5-7 mm</td> </tr> <tr> <td style="text-align: right;"><b>210-7323</b></td> <td style="text-align: left;">7-12 mm</td> </tr> </table>	Stock No:	Cable dia.	<b>210-7322</b>	4.5-7 mm	<b>210-7323</b>	7-12 mm		<p style="text-align: center;"><b>External-threaded 90° Cable-Mount</b></p>  <table style="width: 100%; margin-top: 5px;"> <tr> <td style="text-align: right;">Stock No:</td> <td style="text-align: left;">Cable dia.</td> </tr> <tr> <td style="text-align: right;"><b>210-7309</b></td> <td style="text-align: left;">4.5-7 mm</td> </tr> <tr> <td style="text-align: right;"><b>210-7310</b></td> <td style="text-align: left;">7-12 mm</td> </tr> </table>	Stock No:	Cable dia.	<b>210-7309</b>	4.5-7 mm	<b>210-7310</b>	7-12 mm						
Stock No:	Cable dia.																					
<b>210-7322</b>	4.5-7 mm																					
<b>210-7323</b>	7-12 mm																					
Stock No:	Cable dia.																					
<b>210-7309</b>	4.5-7 mm																					
<b>210-7310</b>	7-12 mm																					
		<p style="text-align: center;">Use Sealing Cap No: <b>210-7925</b></p> 		<p style="text-align: center;">Use Sealing Cap No: <b>210-7924</b></p> 		<p style="text-align: center;">Use Sealing Cap No: <b>210-7925</b></p> 