

PRODUCT NUMBER: 1013941

# Leightning L3HV Hi-Visibility **Headband Earmuff**

Learn more about our products at howardleight.com

Honeywell

# **Overview**

### **Reference Number**

1013941

### **Product Type**

**Hearing Protection** 

# Range

Earmuffs

### Line

Noise Blocking Earmuffs

Howard Leight by Honeywell

### Brand formerly known as

**BILSOM** 

### Industry

- Industry
  Administration
  Agriculture
  Army Defence
  ATEX environment
- Automotive and Part Manufacturer
  Aviation
  Building and Construction
  Catering
- Chemical Industries
  Energy or Electricity
  Fire Protection brigades
  Fishing
  Food Industries
- Foundry Glass Industries Green Spaces Homeland defense Industrial Cleaning
- Iron and steel industry Laboratory Logistics Maintenance Medical and Pharmaceutical
- Metal steel
  Minning and Quarrying
  Offshore
  Paper Industries
  Petro-chemical
- Printing Industries Services Ship Building Telecoms Textile Industries Transportation
- Utilities Water treatment Welding Wood Industries

# **Product Use**

# **NOISE-BLOCKING EARMUFF**

For Aviation and Construction Industries where Hi-Visibility is needed

# **Features & Benefits**

### **Feature**

BRIGHT GREEN EARCUPS Provides additional high visibility and contrast on the job. Ideal to wear at night, during the day, in low light, and under inclement weather conditions. Bright green color does not fade when exposed to sunlight.

# Leightning L3HV Hi-Visibility Headband Earmuff - 1013941

REFLECTIVE HEADBAND Reflective material highly visible under light for increased visibility and safety, especially in low lighting. Delivers long-wearing comfort. Minimal headband pressure on the head. AIR FLOW CONTROL TECHNOLOGY Bilsom's patented Air Flow Control™ technology delivers optimal attenuation across all frequencies, without increasing earcup size or weight. A patented baseplate chamber and high-tech non-woven layer manage the flow of air inside the earmuff to control how sound reaches the ear. The result is better, more consistent overall attenuation for virtually all industrial noise environments. STEEL WIRE CONSTRUCTION Robust steel headband withstands demanding use, especially in tough environments. SNAP-IN EAR CUSHIONS Snap-in ear cushions make replacement quick and easy. PADDED FOAM HEADBAND delivers long-wearing comfort with minimal pressure on the head.

#### Benefit

When the jobsite is outdoors or in low lighting, workers are exposed to increased safety hazards in addition to noise. Bilsom LEIGHTNING HI-VISIBILITY Earmuffs provide workers with a total solution for both hearing protection and visibility at night – and during the day. Its eye-catching bright green earcups provide a highly noticeable contrast against dark settings, especially in low lighting situations and inclement weather. Plus, LEIGHTNING HI-VISIBILITY are the only earmuffs that incorporate an exclusive reflective headband that glows when exposed to light, providing increased visibility and safety on the job.

# **Technical Description**

SNR (dB)

34

H (dB)

33

M (dB)

32

L (dB)

27

#### **Attenuation Data**

| Frequency (Hz) Frequenz (Hz) Fréquence (Hz)                                   | 63   | 125  | 250  | 500  | 1000 | 2000 | 4000 | 8000 |
|---|------|------|------|------|------|------|------|------|
| Mean Attenuation (dB) Mittlere Dämmung (dB) Atténuation moyenne (dB)          | 23.6 | 24.6 | 27.8 | 32.6 | 37.4 | 35.2 | 38.8 | 35.8 |
| Standard Deviation (dB)<br>Standardabweichung (dB) Déviation<br>standard (dB) | 6.4  | 3.6  | 2.0  | 2.0  | 3.3  | 3.2  | 3.1  | 3.3  |
| Assumed Protection (dB) Angenommener (dB) Protection supposée (dB)            | 17.2 | 21.0 | 25.8 | 30.6 | 34.1 | 32.0 | 35.7 | 32.5 |

### **Earmuff Construction**

Metal

### Other Material

Steel Wire, PUR-E, PVC, Textile, PC/PBT, ABS

Dielectric

No

Color

Bright Green, Reflective Tape, Black and Grey

**Batteries Needed** 

None

Weight (grs)

302

**Headband Style** 

Over-Head

**Sound Amplification** 

No

AM/FM Radio

No

**Automatic Shut-Off Function** 

No

**Audio Input Jack** 

Nο

**Hi-Visibility** 

Yes

# Certifications

**EC Category PPE** 

2

**Quality Assurance** 

ISO 9001 / 2000

**EC Certificate Number** 

1294

**EC** Attestation

**EC** Attestation

**EC Attestation Number** 

041108

# **Literature & Documents**

**PIC SKU - Pictures** 

http://www.honeywellsafety.com/assets/0/324/500/51887/d9d8fe85f0404f289ccdbd190f2efa8b.jpg

# **Maintenance**

# Life Cycle

Cushions should be replaced periodically to retain maximum attenuation. Use the following as a guideline for replacement of ear cushions and insert foam. General use and wear - Ear cushions and foam inserts should be replaced at least every 6 months. Heavy use or wear in humid/extreme climates - Ear cushions and foam inserts should be replaced at least every 3 months. Cracking or leakage is visible - replace ear cushions and foam inserts immediately.

### **Storage Information**

When not in use, the earmuffs should be stored in a clean dry container or locker. Do not use solvents or petroleum-based products. Do not immerse the earmuffs in water.

### **Care Instructions**

Earmuffs are an important safety product and should be inspected regularly. Its use, care and maintenance are critical to its effective performance. Earmuffs and in particular ear cushions may deteriorate with use and should be examined at frequent intervals for cracking and leakage. If the ear cushions become hard, damaged or deteriorated, they should be replaced promptly using recommended Hygiene Kits. Earmuffs should be maintained by regular cleaning. Use a mild disinfectant solution. A gentle wipe is all that is required.

# Parts & Accessories

### Accessories

Hygiene Kit - Packed in a plastic bag, including two ear cushions and two liners. Ref. # 1012000 for L3, L3H, L3N Beltclip - For carrying purpose. Old Ref. # 1000252 New Ref. # 1016730 Cool II Pads - Sweat absorbing pads. Ref. # 1000365 5-pair, Ref. # 1000364 100-pair

Optisorb - cotton sleeve slides over earcup. Ref. # 3302101 Polar Hood - Ref. # 1016870 Lg/XLg; Ref. # 1016871 Sm/Med

# **Packaging**

**EAN Code** 7312550139417

© Honeywell International Inc.