

Accessories Cords Series

Specification Sheet

PRODUCT DESCRIPTION:

MCR Safety offers a wide variety of products to assist in the care and maintenance of your safety eyewear. The 214 eyewear cord helps you keep up with your safety glasses in style. The plastic tips on this lanyard snaps into place over the dimples found on the eyewear temples. This allows the cord to break away from the glasses should they become entangled and pulled. An easy to use take-up cinch slide allows for easy adjustability. Non dielectric - metal clamps.

FEATURES:

212

- Black eyeglass cord
- Clip on / Break away design
- Clips on to dimples found on temple tips
- Black stretchable cord
- Take-up cinch slide allows adjustability



10.163 lb.

N/A

N/A

TECHNICAL DATA FOR: 214

Series Accessories
Category Cords

Packaging Clear Plastic Bags

Case Pack 600

N/A

N/A

Case Dimensions 17.323 x 11.417 x 7.480 **Made In** Taiwan

No

Lens Scratch Frame **Temple Temple** Item No: Lens Coating: VLT%: Options: Resistant: Color: Color: Sleeve: 200 N/A N/A No N/A N/A N/A N/A 201 N/A N/A No N/A N/A N/A N/A 202 N/A N/A No N/A N/A N/A N/A 203 N/A N/A N/A N/A N/A No N/A 204 N/A N/A No N/A N/A N/A N/A 207 N/A N/A No N/A N/A N/A N/A N/A N/A 208 N/A No N/A N/A N/A 208G N/A N/A No N/A N/A N/A N/A 210 N/A N/A N/A N/A N/A N/A No

Case Weight

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrsafety.com

N/A

N/A



Accessories Cords Series

Specification Sheet

Lens	Lens Coating:	Scratch Resistant:	VLT %:	Frame	Temple	Temple
Options:				Color:	Color:	Sleeve:
N/A	N/A	No	N/A	N/A	N/A	N/A
N/A	N/A	No	N/A	N/A	N/A	N/A
N/A	N/A	No	N/A	N/A	N/A	N/A
N/A	N/A	No	N/A	N/A	N/A	N/A
N/A	N/A	No	N/A	N/A	N/A	N/A
N/A	N/A	No	N/A	N/A	N/A	N/A
N/A	N/A	No	N/A	N/A	N/A	N/A
N/A	N/A	No	N/A	N/A	N/A	N/A
N/A	N/A	No	N/A	N/A	N/A	N/A
N/A	N/A	No	N/A	N/A	N/A	N/A
N/A	N/A	No	N/A	N/A	N/A	N/A
N/A	N/A	No	N/A	N/A	N/A	N/A
N/A	N/A	No	N/A	N/A	N/A	N/A
N/A	N/A	No	N/A	N/A	N/A	N/A
N/A	N/A	No	N/A	N/A	N/A	N/A
N/A	N/A	No	N/A	N/A	N/A	N/A
N/A	N/A	No	N/A	N/A	N/A	N/A
N/A	N/A	No	N/A	N/A	N/A	N/A
N/A	N/A	No	N/A	N/A	N/A	N/A
N/A	N/A	No	N/A	N/A	N/A	N/A
N/A	N/A	No	N/A	N/A	N/A	N/A
N/A	N/A	No	N/A	N/A	N/A	N/A
N/A	N/A	No	N/A	N/A	N/A	N/A
N/A	N/A	No	N/A	N/A	N/A	N/A
N/A	N/A	No	N/A	N/A	N/A	N/A
N/A	N/A	No	N/A	N/A	N/A	N/A
N/A	N/A	No	N/A	N/A	N/A	N/A
N/A	N/A	No	N/A	N/A	N/A	N/A
N/A	N/A	No	N/A	N/A	N/A	N/A
	Options: N/A N/A	Options: Lens Coating: N/A N/A N/A N/A	Options: Lens Coating: Resistant: N/A N/A No N/A N/A No </td <td>Options: Lens Coating: Resistant: N/A N/A No N/A N/A N/A No N/A</td> <td>Options: Lens Coating: Resistant: VLT %: Color: N/A N/A N/A N/A N/A N/A</td> <td>Options: Lens Coating: N/A Resistant: VL1%: N/A Color: N/A N/A N/A</td>	Options: Lens Coating: Resistant: N/A N/A No N/A N/A N/A No N/A	Options: Lens Coating: Resistant: VLT %: Color: N/A N/A N/A N/A N/A N/A	Options: Lens Coating: N/A Resistant: VL1%: N/A Color: N/A N/A N/A