

V-1250i HEAVY DUTY

Stick Welding
Power Source

Quick Specs

Industrial Applications

Construction
Process Piping
Maintenance
Shipbuilding

Power Voltage

3 Phase AC415V ±15%
50/60Hz

Input Current
91A/65.4kVA

Output Range

100-1000A

Output Voltage

60V
Max. OCV: 83VDC

Duty Cycle

80%

Weight

83KG

Dimensions

D770×H945×W500MM

**Portable. Professional.
Rugged. Affordable.**

HEAVY DUTY

FEATURES

- **Arc Force** minimizes electrode sticking in the puddle without compromising arc stability or increased spatter.
- **Hot Start** boosts the current during starting to make striking an arc easier.
- **Thermal overload protection with indicator light** helps prevent machine damage if the duty cycle is exceeded or airflow is blocked.

PROCESSES

Stick (SMAW)
DC TIG (GTAW)
Arc Gouging



INCLUDED

V-1250i Machine Only Includes:

- V-1250i

INPUT



OUTPUT



**Please note that the specification may vary within each country. Specifications are subjected to change without notice.*

AUSTCORP MANUFACTURING SDN. BHD.

NO. 8 & 10 PERSIARAN BATU GAJAH PERDANA 3
TAMAN BATU GAJAH PERDANA
31550 PUSING PERAK MALAYSIA
TEL: (605)3632 115 FAX: (605)3632 111
E-mail: austcorp@welding.com.my
WEB: www.welding.com.my



Welding Technology