

TOP PLATE - MEDIUM HEAVY DUTY

# 400 PC SERIES

320 ~ 440 KGS

In Compliance to Korean Standard Specification

## Castor 400

Made of hardened steel. Welded double ballrace swivel head  
Metal Parts: Galvanized (grease nipple)  
Plate with 6 holes

## Wheel PC

PC mold on polyurethane cast-iron centre (durometer: 90 ±5° Shore A)  
Round profile PU. Precision ball bearing with steel threadguards  
Temperature Range: -40°C to +80°C




Manufactured by Kyung Chang Korea



Swivel	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	bearing	Safety kgs	Max kgs
<b>4040S-A1-PC</b>	100x114	71x84	M10	143	81	102	48	17	57	6203	320	350	
<b>4050S-A1-PC</b>	100x114	71x84	M10	165	98	127	48	17	57	6203	360	400	
<b>4060S-A1-PC</b>	100x114	71x84	M10	190	115	152	48	17	57	6203	380	420	
<b>4080S-A1-PC</b>	100x114	71x84	M10	241	152	203	48	17	57	6203	400	440	



Rigid	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	bearing	Safety kgs	Max kgs
<b>4040R-A1-PC</b>	100x114	71x84	M10	143	Rigid	102	48	17	57	6203	320	350	
<b>4050R-A1-PC</b>	100x114	71x84	M10	165	Rigid	127	48	17	57	6203	360	400	
<b>4060R-A1-PC</b>	100x114	71x84	M10	190	Rigid	152	48	17	57	6203	380	420	
<b>4080R-A1-PC</b>	100x114	71x84	M10	241	Rigid	203	48	17	57	6203	400	440	



Side-Brake	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	bearing	Safety kgs	Max kgs
<b>4040S-A1-TB</b>	100x114	71x84	M10	143	81	102	48	17	57	6203	320	350	
<b>4050S-A1-TB</b>	100x114	71x84	M10	165	98	127	48	17	57	6203	360	400	
<b>4060S-A1-TB</b>	100x114	71x84	M10	190	115	152	48	17	57	6203	380	420	
<b>4080S-A1-TB</b>	100x114	71x84	M10	241	152	203	48	17	57	6203	400	440	



Total-Brake	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	bearing	Safety kgs	Max kgs
<b>4040S-A1-TTL</b>	100x114	71x84	M10	143	81	102	48	17	57	6203	320	350	
<b>4050S-A1-TTL</b>	100x114	71x84	M10	165	98	127	48	17	57	6203	360	400	
<b>4060S-A1-TTL</b>	100x114	71x84	M10	190	115	152	48	17	57	6203	380	420	
<b>4080S-A1-TTL</b>	100x114	71x84	M10	241	152	203	48	17	57	6203	400	440	



Wheel	profile	mm	mm	mm	mm	bearing	Safety kgs	Max kgs
<b>PC4040</b>	Round	102	48	17	57	6203	320	350
<b>PC4050</b>	Round	127	48	17	57	6203	360	400
<b>PC4060</b>	Round	152	48	17	57	6203	380	420
<b>PC4080</b>	Round	203	48	17	57	6203	400	440