




Metric Lugs and Splices T&B Catalog Number:

UPC Number: Status: Description: MCC6M6 78621095749 Active

Copper One-Hole Metric Lug, Standard Barrel, Peep Hole, Max 35kV, 6mm Wire, 6mm Bolt Size, Tin Plated Features



	Manufactured from seamless copper tubing that
	conforms to BS2781 with heavy-duty wall thick-
	ness, achieving maximum conductivity with low re-
	sistance.
	Electro Tin-Plated for Corrosion Resistance. Cham- fered Barrels Provide Ease of Strand Entry and In- spection hole facilitates full insertion of the conduc- tor.
	Cable Area Clearly Identified on Lug.
General	
Style	Metric Standard Barrel Copper Lug
Material	Copper
Finish	Tin Plated
Wire Size	6mm
Number of Studs	1
Tongue Angle	Straight
Barrel Length	Standard
Barrel Shape	Standard
Tongue Width	Standard
Peep Hole	Y
Marking	Standard
Hole Shape	Round
Dimension Information	
A (mm)	25.5
B (mm)	7.0
C (mm)	11.0
D (mm)	3.6
F (mm)	6.0
Specifications	
Temperature Rating	105°C
Voltage Rating	600V
Tooling	
Connector & Tooling Chart	Available on Website
Packaging	
T&B Order Multiple	100
T&B Inner Pack	100
Package in Units	1000
T&B Sold in UOM	Each
T&B Weight Per UOM	5.63 lbs. per 1000
Application Support	
T&B Sales Drawings	wsd-000151



Notes

Dimensions given for reference only. Dimensions may vary up to +/-.030.

Certifications

RoHS Compliance	Yes
Webcat CE_recognized	Υ

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com