

FEATURES

- 22 to 8 AWG wire range
- UL94V-0 flammability rating
- Designed in accordance with IEC685
- Terminations marked Live, Neutral & Earth
- Conductor terminates in screw-down clamp

RS PRO, 3 Way, 22 → 8 AWG, Nylon Non-Fused Terminal Block, 450V

RS Stock No.: 465-637



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

RS PRO 3 way non-fused terminal block with screw down mounting type. This pluggable terminal block lets you to carry out mounting and start up quickly.

General Specifications

Fused	No
Mounting Type	Screw Down
Termination Method	Screw Down
Material	Nylon
Number of Ways	3
Housing	Brown glass filled polyamide 6.6
Applications	Connecting lighting to switches, Connecting wiring to a ground, HVAC Systems, Power Supplies

Electrical Specifications

Current Rating	40A
Voltage Rating	450V

Mechanical Specifications

Cable CSA	6mm ²
Wire Size	22AWG to 8AWG
Height	24mm
Width	31.5mm
Length	81.3mm
Pitch	17.7mm
Screw Size	M5 x 10

Operation Environment Specifications

Minimum Operating Temperature	-5°C
Maximum Operating Temperature	150°C

Approvals

Compliance/Certifications	UL recognised, CSA certified and IMQ UL Listed; CSA Certified; NEMKO; DEMKO; SEMKO; SEV; IMQ; KEMA
---------------------------	--

