



Main

Range	Pieno
Product or component type	Fused connection unit
Rated current	13 A at 250 V AC 50 Hz
Load type	Resistive
Protection type	Fuse
Number of gangs	1 gang
Cover frame colour tint	White

Complementary

Wiring device mounting	Surface Flush
Material	Polycarbonate: surround Polycarbonate: grid plate
Clamping connection capacity	1 x 2.5 mm ² for solid cable(s) 2 x 4 mm ² for stranded cable(s)
Connections - terminals	Folded terminal
Width	87 mm
Height	87 mm
Depth	27.8 mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	BS 1363

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.78 cm
Package 1 Width	8.7 cm
Package 1 Length	8.7 cm
Package 1 Weight	103.03 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	9.5 cm
Package 2 Width	15 cm
Package 2 Length	19 cm
Package 2 Weight	1.03 kg
Unit Type of Package 3	CAR
Number of Units in Package 3	100
Package 3 Height	21 cm
Package 3 Width	32.5 cm

Package 3 Length	50 cm
Package 3 Weight	11887.6 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------