



Datasheet

ENGLISH

RS Pro Grey F2000 Panel Trunking W40XH40

RS Stock No: 136-9105

The Control Panel Trunking F 2000 is extrusion-made out of rigid- PVC and will be punched.

Characteristic:

| | |
|------------------------|--|
| Material: | rigid-PVC lead-, silicon- and cadmium-free (RoHS conform) |
| Operation temperature: | static: -20°C...+60°C (permanently) -30°C...+75°C (briefly) |
| working temperature: | Dynamic: -5°C...+60°C >0°C |
| Fire behaviour: | hard to inflame according to DIN 4102; Level B1 Self-extinguishing according to UL94; V0 Fire load: 5,2 kWh/kg |
| Dielectric strength: | >30kV/mm |
| UV resistance: | PVC is conditionally permanent to UV-light, changes in colour under UV-light can not be excluded |
| Colour: | RAL 7030 gray |
| Delivery length: | 2000 mm with cover |

Special property:

- Cover contour 90°
- Ideal fit of cover, easy assembly and disassembly
- Smooth fingers – will not hurt the installer or damage the cables
- Cable hold-back noses from installation height 60 mm onwards
- Web Thickness 5,5 mm; slot width 4,5 mm
- Notch points at the slides and base of trunkings
- Perforated base according to DIN 50085-2-3, identical punch picture for each length
- 3- lanes hole pattern starts at width 80 mm
- Attachments and more information's you will find under www.licatec.de



Dimension:

| F2000 | Height (H) in mm | Width (W) in mm | | | | | | | |
|-------|---------------------|-----------------|----|----|----|-----|-----|------|--|
| | 30 | 30 | | | | | | | |
| 40 | 25 | 30 | 40 | 60 | | | | | |
| 60 | 25 | 30 | 40 | 60 | 80 | 100 | 120 | 200* | |
| 80 | 25 | 30 | 40 | 60 | 80 | 100 | 120 | | |
| 100 | | 30 | 40 | 60 | 80 | 100 | | 150 | |
| 120 | | | 40 | 60 | 80 | | | | |

* Dimension 200x60 mm with a different punch picture

