

Datasheet

RS Pro Toggle Switch SPDT On-None-On, 5 A @ 250 V ac, PCB

RS Stock No: **401-703**



Product Details

RS Pro SPDT toggle switch has epoxy sealed terminals to prevent contamination during soldering. This PCB switch performs on-on operation. It withstands currents up to 5 A at 250 V ac voltage. The copper alloy contacts offer superior performance.

Features and Benefits

- Epoxy sealed terminals prevent contamination during soldering
- Chrome plated brass actuator
- Diallyl phthalate (DAP) case (UL94V-0)
- Silver contacts

**Specifications:**

Actuator Length	10.41 mm
Actuator Material	Chrome Plated Brass
Contact Configuration	SPDT
Contact Current Rating	5 A at 125 V ac or 28 V dc, 2 A at 250 V ac
Contact Material	Silver Plated Copper Alloy
Contact Resistance	10 mΩ
Maximum Operating Temperature	+85°C
Mechanical Life	40000 cycles
Minimum Operating Temperature	-30°C
Mounting Type	PCB Mount
Operating Temperature Range	-30 to +85°C
Standards Met	RoHS & Lead Free
Switch Operation	On-None-On
Terminal Type	PC Through Hole
Bushing Length	8.89 mm
Bushing Style	Keyway (Threaded)
Seal	Epoxy