

#### **FEATURES**

- Body material is AISI 304 stainless steel sheets
- IP66 rating
- Double lipped edges to ensure higher strength and ease of installation
- Easy to use, including removal of the door
- Door is fitted with a polyurethane gasket

# RS PRO Wall Boxes - 304 Stainless Steel Wall Box

RS Stock No.: 7586964



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

### **Wall Boxes**



#### **Product Description**

#### RS Pro IP66 Wall Boxes

Brought to you by RS Pro, a range of stainless steel wall mounted enclosures. Rated at IP66, the level of protection provided by these boxes ensures the contents will be safely stored and protected. The door of the enclosure has a pull out hinge which allows it to be removed for easy access and due to the protection benefit, these wall boxes are suitable for various applications. All models are highly reliable and excellent quality.

#### **General Specifications**

Body Material	304 Stainless Steel				
-	504 Stall 11055 Stoci				
Number Of Doors	1				
Colour	Unpainted				
Gland Plate	No				
Door Lock Type	Quick Release Lock				
Chassis Plate	Yes				
Transparent Door	No				
Fixing Kit	No				
Application	Electrical				
External Mounting Type	Bracket				
Internal Mounting Type	Panel				
Special Features	120° Door Opening				
For Protection Of	Sensitive electrical equipment				

#### **Mechanical Specifications**

External Height	600 mm	
External Depth	200 mm	
External Width	400 mm	
Dimensions	H.600 mm x W.400 mm x D.200 mm	
Weight	17.52kg	

#### **Protection Category**

IP Rating	IP66

# Wall Boxes



# Approvals

## **Similar Products**

Stock No.	Brand	Product Name	Colour	Body Material	Dimensions
758-6974	RS PRO	304 Stainless Steel Wall Box	Unpainted	304 Stainless Steel	400 mm x 300 mm x 150 mm
758-6970	RS PRO	304 Stainless Steel Wall Box	Unpainted	304 Stainless Steel	1000 mm x 800 mm x 300 mm