



Main

Product or component type	Telephone socket
Telephone socket type	RJ11 (4 contacts) - category 3
Colour tint	Grey silver

Complementary

Wiring device mounting	Surface Flush
Socket number	2
Rated current	1.5 A at 125 Vrms AC
Number of gangs	2 gangs
Material	PBT 15 % FG: insert PC: housing Polycarbonate: plastic part
Contacts material	Contact: phosphor bronze IDC contact: phosphor bronze with tin plating
Contact resistance	1000000 μ Ohm
Insulation resistance	\geq 1000 MOhm
AWG gauge	AWG 26...AWG 24 (2 twisted pair cables)
Width	87 mm
Height	87 mm
Depth	36 mm

Environment

Dielectric strength	750 V for 60 s at 60 Hz
Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use
Standards	YD/T 577-92

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.6 cm
Package 1 Width	8.7 cm
Package 1 Length	8.7 cm
Package 1 Weight	92 g
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	15 cm

Package 2 Width	19 cm
Package 2 Length	8 cm
Package 2 Weight	750 g
Unit Type of Package 3	CAR
Number of Units in Package 3	80
Package 3 Height	21 cm
Package 3 Width	31 cm
Package 3 Length	50 cm
Package 3 Weight	8500 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------