

## Datasheet

### Fibre Optic Cable Assembly, Multi-Mode

RS Stock number 535-7446



## Description

Multimode patchcords are used to connect high speed and legacy networks like Gigabit Ethernet, Fast Ethernet and Ethernet. The multimode patchcords are manufactured using LSZH cables which conform to IEC, EIA TIA and Telecordia standards. The OM1 patchcords are terminated with a standard connector which gives optimum optical performance.

## Features

- ▶ SC, LC, ST, FC and MTRJ connectors
- ▶ Low smoke zero halogen (LSZH) cable in orange colour
- ▶ 900µm / 600 µm tight buffer
- ▶ OM1 fibre conforms to ITU-651, TIA/EIA 492AAAA
- ▶ Simplex and duplex assemblies
- ▶ Duplex assemblies available with clips (SC and LC)
- ▶ Different connector performance range for specific application
- ▶ Armoured option also available

## Applications

- ▶ Gigabit Ethernet in high speed LAN networks over an indicative 275 m link length at 850 nm (SX) wavelength
- ▶ Legacy networks including Ethernet, Fast Ethernet and FDDI
- ▶ Data centres
- ▶ Premises cabling in data networks including backbone, riser and horizontal
- ▶ Supports video, data and voice services



**Description**

The ST connector is the most popular connector used today. It can be seen in every area of the communications environment, from a telecoms distribution room to a local area network closet the ST has set the standard for optical fibre connectors.

The Optronics ST connectors are manufactured using the highest quality components. The connectors exceeds all areas of the standards covering optical fibre connectors.

**Versions Available:**

- 2mm Patch
- 3mm Patch
- 900 µm

**Termination Procedures**

Prep cable end, Epoxy-Crimp-Polish

**Product Packaging**

Standard packaging: 100pcs bulk packed  
Special packaging available by request

**Colours**

- 2 & 3 mm Boot, Black, Red, Yellow
- 900 µm Boot, Black, Blue, Yellow

**Intermateability**

Optically and mechanically compatible with all equivalent connectors.

Compliant with IEC 61754-2.

**Optical Performance**

**Singlemode**

Insertion loss: Max. 0.3 dB Typical 0.2 dB

Return Loss: UPC > 50dB Typical 55 dB

**Multimode**

Insertion loss: Max. 0.3 dB Typical 0.12 dB

**Mechanical**

Capillary diameter tolerance:

SM—126 ± 0.5µm

MM—127 =/- 0.5µm

Ferrule Diameter:2.5mm ± .001

Ceramic pre-radiused, PC-end finish for Physical

Contact ferrule to ferrule. R 10 to 25mm

Tensile Strength Cable retention: >50 N

(2 & 3mm boot versions only)

**Vibration (Mated Pair):**

(IEC 61300-2-1)

10-55 Hz, 1.5mm P to P

=0.3dB Change

**Mating Durability:**

(IEC 61300-2-2)

1000 mating cycles

Clean every 25

< 0.2 dB Change

**High Temperature:**

(IEC 61300-2-18)

75°C for 96 hours

=0.2dB Change

**Damp Heat:**

(IEC 61300-2-19)

60°C at 95% RH, 96 hours

=0.2dB Change

**Temperature Cycling**

(IEC 61300-2-48)

-40 to +85°C, 42 cycles

=0.2dB Change

**Operating Temperature**

-40°C to +85°C