

FEATURES

- Housing material: transparent blue polycarbonate
- Maximum operating temperature: 85°C
- Captive screws: galvanized steel
- Protection degree: IP 20
- Self-extinguishing

RS PRO Commoning Block, 5 Way, 450V

RS Stock No.: 868-0774



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.



Product Description

From RS PRO, this compact commoning block is ideal for use in derivation and junction boxes. Not only does its compact design allow for excellent space management, it also has a robust construction with high mechanical resistance. For reliable high-density connections with excellent electrical characteristics, this polycarbonate terminal connector is ideal.

General Specifications

Clamps	Brass
Self-extinguishing	UL 94 - V0; IEC 695-2-1 to 850°C; IEC 695-2-2
Termination Method	Screw
Number of Ways	5
Housing	Transparent blue polycarbonate
Screws	Galvanised steel
Applications	Junction box, Derivation box, Panel boards, Demarcation points, Equipotential earthing

Electrical Specifications

Voltage Rating	450V

Mechanical Specifications

Cable CSA	6mm²
Length	10mm

Operation Environment Specifications

Maximum Operating Temperature	85°C
-------------------------------	------



Protection Category

IP Rating	IP20
-----------	------



Articolo Type	Nr. Poli Ways	Sez. Cond mm ² Conduc. sec. mm ² Flessibile/Rigido Flexible/Rigid	Tensione nominale Rated voltage	Lunghezza spelatura mm Stripping Lenght mm
868-0786	3	1 ÷ 6	450 V	10
868-0774	5	1 ÷ 6	450 V	10
880-6796	Suppor	to per il fissaggio su pi	rofilati / Base	for fixing on rai