

# Datasheet

## Miniature Fuse, Single Cap with Lead Wire

5ØX20mm



Number	Ampere Rating (in)	Voltage Rating (V)	Nominal Resistance Cold Ohms	Voltage Drop (mv) Max.	Nominal Melting I <sup>2</sup> t A <sup>2</sup> Sec
911-3489	1A	250V	0.0744	350	6.9120
911-3483	1.25A		0.0618	300	9.0000
911-3492	1.6A		0.0781	200	6.2640
911-3495	2A		0.0478	190	11.088
911-3499	2.5A		0.0385	180	24.750
911-3509	3.15A		0.0265	140	41.697
911-3502	4A		0.0175	100	95.904
911-3506	5A		0.0130	100	112.50
911-3515	8A		0.0075	100	194.69
911-3518	10A		0.0059	100	331.20

## Electrical Characteristics

Rated Current	2.1 in	2.75 in		4 in		10 in	
	MAX	MIN	MAX	MIN	MAX	MIN	MAX
1A ~ 3.15A	30 min	750 ms	80 sec	95 ms	5 sec	10 ms	150 ms
4A ~ 6.3A	30 min	750 ms	80 sec	150 ms	5 sec	10 ms	150 ms
8A ~ 10A	30 min	750 ms	80 sec	150 ms	5 sec	10 ms	150 ms

## Interrupting Rating

1500 amperes at 250 V ac

## Operating Temperature

-55°C to +125°C

## Physical Specification

### Material

Ceramic body / Nickel Plated Brass Caps

Lead Wire: Diameter  $\varnothing 0.65\text{mm}$  6.3A and less.

Diameter  $\varnothing 0.8\text{mm}$  8A/10A

## Dimensions

