## Product data sheet Characteristics

# SEA9BN24PEV

Acti9 Isobar B - pan assembly - 24 ways TP + earth + neutral





Main	
Range	Acti9
Product or component type	Pan assembly
Device application	Distribution

#### Complementary

Complementary	
Range compatibility	Acti 9 (Acti9 Isobar B) distribution board
Provided equipment	Mounting plate
	DIN rail
	Neutral bar
	Grounding bar
[In] rated current	250 A
Incomer device options	4P switch disconnector
	4P terminal block
	3P + N RCCB
	3P + N MCCB
	4P contactor
Protection device options at outgoer	Residual current circuit breaker with overcurrent protection (RCBO) 45 A max
	Miniature circuit breaker (MCB) 63 A max
Number of ways	24 ways (outgoer)
	1 way (incomer) - 3P + N + E
Outgoer Pole capacity	72 x 18 mm
Length	896 mm
Width	350 mm
Depth	105 mm

#### **Packing Units**

r doking office	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.0 cm
Package 1 Width	39.0 cm
Package 1 Length	92.0 cm
Package 1 Weight	6.18 kg
Unit Type of Package 2	PAM
Number of Units in Package 2	24
Package 2 Height	112.0 cm
Package 2 Width	100.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	247.28 kg

### Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS  Declaration
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Halogen content performance	Halogen free plastic parts product